

TMR-5006

EN50155 Multifunction VPN Router up to 2 LTE 4G + 2 serial ports + 6 Gigabit X-coded Ethernet Switch w/Load Balancing, VPN, Protocol Gateway, Storage**; WV input**

- Built-in 6 Gigabit X-coded Ethernet managed switch; Up to 2x LTE 4G Module (4SIMS)
- VPN router for Multi-site VPN, OpenVPN, L2TP, IPsec, PPTP**, L2 over GRE
- Load Balancing** support 8 mechanism
- Optional EMMC Flash storage on-board**
- Support NAT and Firewall
- Support Modbus gateway on serial ports
- Support 2 RS422/485 ports with 2.5KV isolation or 2x RS232 ports
- Optional 2 GT smart bypass protection
- Galvanic isolation on WV model from 16.8V~137.5V input
- Environmental monitoring for router inside info with voltage, current, temperature; LTE signal strength & TX/RX rate display
- Editable login page of captive portal for hot-spot application
- IP 65 /54 Aluminum housing for best heat dissipation and preventing moist ingress
- EN50155/61373/45545 verification for railway application
- USB port for backup, restore the configuration file and upgrade firmware*; Dual image firmware*



OVERVIEW

Lantech TMR-5006 series is a next generation EN50155 multi-function VPN router w/ 1 x 802.3ac Wi-Fi + 1 x LTE modem +6 Gigabit X-coded Ethernet switch + 2 serial ports that supports advanced function of VPN, Load-balancing**(Premium pack), EMMC Flash Storage**, Protocol gateway(Modbus), Storage**, and LTE dual SIM fail-over for industrial applications. The dual core CPU with 1.6GHz + 256M flash enables the router to multi-task smoothly.

Dual concurrent LTE design 4G/3G for load-balancing

With dual LTE module design (2L model), 4 SIM card slots, TMR-5006 can allow auto-swap, failover & fallback between multiple service providers for real non-stop connection. With concurrent LTE modules, it can also allocate bandwidth by " Load Balancing** with 8 schemes between multiple WANs. Both GPS and Russian GLONASS systems are supported.

Optional EMMC Flash storage**

The optional EMMC flash storage on router can offer 8G/16G/32G capacity.

Load Balancing** with 8 mechanism for multi-WANs (premium license)

TMR-5006 supports Load Balancing** for LTE/WAN connections. There are eight schemes for Load Balancing**

function:

Pack	Algorithm	Description
Standard	Fixed	Manually route by traffic type through fixed WAN link.
Basic Package	Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activate another link if preferred link fail occurs. Once failover will not fallback until link loss.
	Priority	Routes connections through preferred WAN link as primary while others follow by. Ex. Wi-Fi client>LTE>others
	Weighted Round-Robin	Evenly distribute the traffic over all working WAN links in circular order according to the specified weights.
	Custom	Routing through the selected

	Route	WAN for each specific traffic, ex: TCP/UDP port number and IP address.
Full Package (incl. basic package)	Sticky Session*	Binding all connections in an application session to particular WAN link to ensure all connections in the session are routed to the same WAN link, that is suitable for security services like online payment etc.
	Smallest Load*	Routes connections through the WAN link with highest free bandwidth ratio. The ratio = 1 - (traffic load / the capability of a WAN link). The traffic load could be defined by downstream, upstream or total traffic
	Fastest*	Routes connections through the WAN link with lowest latency time.

2 port serial connection, Modbus gateway

It builds in 2 port serial connection for RS232; RS422/ 485 in which RS422/485 has 2.5KV isolation protection.

The built-in Modbus gateway can convert Modbus RTU/ASCII to Modbus TCP for device control.

VPN and firewall

Besides traditional VPN peer to peer tunneling, TMR-5006 support latest Multi-Site VPN function that is an efficient way for mesh tunneling. The registration is under cloud service and encrypted by SSH makes the connection easy and safe.

It supports Multi-Site VPN, Open VPN, L2TP, IPsec L2 over GRE, NAT, and PPTP** for various VPN applications.

The built-in Layer-4 firewall includes DoS**, IP address filter / Mac address filter* / TCP/UDP port number.

Optional 2 GT smart bypass protection

The optional bypass relay is set to bypass the router to the next one when power is off in order to protect the network from crashing. Lantech bypass caters to remain in bypass mode until the router is completely booting up when power is back to avoid another network lost. Also it will be activated when detecting the router is hanged or link down.

DIDO for alarm & email notice; Event log; Remote Web/SMS** control**

2 sets of DIDO function can support additional high/low

physical contact for designate applications besides Port / Power events, for example, DIDO function can trigger alarm if the router was moved or stolen. In case of events, the TMR-5006 will immediately send email** and trap.

The event log can be sent via syslog, email**s or trigger the alarm relay.

When the router is at remote area with limited access, Web/SMS** control can help to get router status or remotely reboot by Web/SMS**

Wide range dual isolated input voltage from 16.8-137.5V (WV model)

The TMR-5006 is able to work from dual 16.8V ~137.5V DC isolated input (WV model) that is particular good for vehicle, rail train, depot etc applications.

Environmental monitoring for inside router info& alerting; LTE signal strength and TX/RX rate display

The built-in environmental monitoring can detect router ambient temperature, voltage, current where can send the syslog, email** and SMS** alert when abnormal.

The LTE signal strength and TX/RX rate display shows connection status at a glance

Built-in Managed Switch Function

Managed switch function is built-in and provides various L2+ functions for network access deployment. It delivers ports and PoE management, VLAN, QoS, multicast, redundant ring, and security functions.

Editable login page of captive portal

Editable login page of captive portal

The TMR-5006 supports editable captive portal function that allows administrator to force end-users redirect to authentication page.

USB port for back up, restore configuration and upgrade firmware*; Dual image firmware*

The built-in USB port can upload/download the configuration through USB dongle for router replacement
It supports dual-image firmware* to choose which one to start.

Ruggedized EN50155 design and FCC*/CE* & E-marking certificate**

The TMR-5006 series is verified with EN50155*, EN61373*, EN45545 standard with IP65/54 housing. It passed tests under extensive Industrial EMI and environmental vibration and shocks standards. With CE* & FCC* LTE and E-marking** certificate, the TMR-5006 is best for outdoor community, vehicle, power substation, process control automation etc. For more usage flexibilities, TMR-5006 supports operating temperature from -20°C to 75°C or -40°C to 75°C(-E)

FEATURES & BENEFITS


- Dual DC input from 16.8V~137.5VDC isolated power input (WV model)
- Optional 2 GT smart bypass relay protection when detecting power lost as well as CPU hang-up or link down. Deferring bypass time until router is completely boot-up.
- EMMC-FLASH storage**8/16/32G
- 6 STANDARD SMA / OPTIONAL QMA type connectors
- Support IPv6** & IPv4 protocol
- Radius Authentication, EAP-MD5, EAP-TLS, EAP-TTLS, PEAP;
- Support Multi-Site VPN for mesh tunneling as well as Open VPN, L2TP, IPsec L2 over GRE, and PPTP** fro secured network connection
- The built-in Layer-4 firewall includes DoS**, IP address filter / Mac address filter* / TCP/UDP port number.
- Support SNMP*v1/v2c/v3
- Support NAT/DMZ
- One LTE 4G/3G w/ 2 SIM card design(1L model) for mobile redundancy
- GPS/ GLONASS (built-in LTE module) connection
- Load Balancing** supports 8 mechanism between multiple WANs

Package (incl. basic package)	Session*	application session to particular WAN link to ensure all connections in the session are routed to the same WAN link , that is suitable for security services like online payment etc.
	Smallest Load*	Routes connections through the WAN link with highest free bandwidth ratio. The ratio = 1 - (traffic load / the capability of a WAN link). The traffic load could be defined by downstream, upstream or total traffic
	Fastest*	Routes connections through the WAN link with lowest latency time.

- Built-in 2 x serial ports(RS232/RS422/485)
- Serial port with 2.5KV isolation on RS422/485
- Supports 2DI/ 2DO(Digital Input / Output)
- Built-in Modbus gateway converting Modbus RTU/ASCII to Modbus/TCP for serial ports
- Event alerting by Syslog, Email**, SMS** text, Relay ; Permanent local log rotation / Maxi 1K records
- Remote Web/SMS** control to get status or re-boot by Web or SMS*
- Support SNTP to synchronize system clock
- Support LLDP discovery protocol
- Support DHCP Server and Client
- LTE signal strength & TX/RX rate display
- Built-in environmental monitoring for system input voltage, current and ambient temperature; Able to set alert when abnormal
- Firmware upgradeable through TFTP/FTP/HTTP
- Configuration backup and restoration
 - Supports text configuration file for system quick installation
 - USB port to upload/download configuration by USB dongle
- Dual image firmware*
- IP 65/54 housing for water proof environment
- Wall-mount installation
- Support editable captive portal login page
- Visible LED to show the power & port link and activity
- Operation temperature -20~75C or -40~75C(-E)

Pack	Algorithm	Description
Standard	Fixed	Manually route by traffic type through fixed WAN link.
Basic Package	Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activate another link if preferred link fail occurs. Once failover will not failback until link loss.
	Priority	Routes connections through preferred WAN link as primary while others follow by. Ex. Wi-Fi client>LTE>others
	Weighted Round-Robin	Evenly distribute the traffic over all working WAN links in circular order according to the specified weights.
	Custom Route	Routing through the selected WAN for each specific traffic, ex: TCP/UDP port number and IP address.
Full	Sticky	Binding all connections in an

DIMENSIONS (unit=mm)



SPECIFICATION

Cellular Interface		Software	
Location Solutions	GPS, Glonass (EU/Americas) GPS, Glonass, Beidou, Galileo (APAC model only)	IPv6/4	Present
Band Options	APAC & Australia (APAC model) LTE: 2100/1800/850/2600/900/850/850/1500/750/2600/1900/2300/2500 MHz (B1/B3/B5/B7/B8/B18/B19/B21/B28/B38/B39/B40/B41)	Login Security	Supports IEEE802.1x** Authentication/RADIUS
	EUNA & USA model LTE: 2100/1800/2600/900/800 MHz (B1/B2/B3/B4/B5/B7/B12/B13/B20/B25/B26/B29/B30/B41)	Access Security	HTTP/HTTPS/Telnet/SSH & Administration; SNMP*v1/v2/v3 access for authentication via MD5/SHA(v3) and Encryption via DES/AES(v3)
	WorldWide (WW model) LTE: 2100/1900/1800/1750/850/2600/900/1800/750/750/850/850/800/850/750/2300/1500/2500/3500/3750/520/3600/1750 (B1/B2/B3/B4/B5/B7/B8/B9/B12/B13/B18/B19/B20/B26/B28/B29/B30/B32/B41/B42/B43/B46/B48/B66)	Protocol	PPPoE Client,DHCP server/client, Adjustable MTU, Port forwarding (NAPT), DMZ, NAT, SNTP, Firewall(Firewall(DoS**); IP address filter / Mac address filter* / TCP/UDP port number),VRRP**, DDNS*
		Management	SNMP*v1, v2c, v3/ Web/Telnet/CLI
Data Rates – LTE	APAC & Australia (APAC model) Downlink (Cat 6): FDD: 300 Mbps TDD: 222 Mbps Uplink (Cat 6): FDD: 50 Mbps TDD: 26 Mbps	Load Balancing**	8 schemes for multiple WAN
		Fixed	Manually route by traffic type through fixed WAN link.
		Basic Package**	
		Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activate another link if preferred link failure occurs.
	Priority	Routes connections through preferred WAN link while others stand-by. Sequentially activate other links if overflow occurs.	
	Weighted Round-Robin	Evenly distribute the traffic over all working WAN links in circular order according to the specified weights	
	Custom Route	Routing through the selected WAN for each specific traffic ex: TCP/UDP port number and IP address.	
	Full Package incl. basic package**		
	Sticky Session*	Binding all connections in an application session to particular WAN link to ensure all connections in the session are routed to the same WAN link , that is suitable for security services like online payment etc.	
	Smallest Load*	Routes connections through the WAN link with highest free bandwidth ratio. The ratio = 1 - (traffic load / the capability of a WAN link).	

	The traffic load could be defined by downstream, upstream or total traffic	DI/DO	2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 40 VDC, 200mA
Fastest*	Routes connections through the WAN link with lowest latency time.	EMMC Storage**	8/16/32 GB
Authentication	Radius Authentication, EAP-MD5, EAP-TLS, EAP-TTLS, PEAP	LED Indicators	
Timer	Built-in Real Time Clock to keep track of time always(RTC)	Power & System indicator	Per unit: Power 1 (Green), Power 2 (Green), P-Fail (Red) , Ring Master(Green), System Ready(Green), Serial1/Serail2(Green) ,
Discovery	IEEE 802.1ab Link Layer Discovery Protocol (LLDP)	10/100/1000Base-T(X) port indicator	Link/Activity (Green), Speed (Yellow)
SNMP trap	Device cold / warm start Port link up / link down DI / DO high / low	SIM	Green for Link/Act
Environmental Monitoring	System status for input voltage, current , ambient temperature to be shown in GUI and sent alerting if any abnormal status	GPS	Green for Link/Act
signal display	LTE signal strength & TX / RX rate display	Fault	Red: Ethernet link down or power down
Remote Web/SMS** control	To reboot or get status of router by Web/SMS**	Fault contact	
Captive portal	Editable captive portal login page	Relay	Relay output to carry capacity of 1A at 24VDC
Maintenance	Firmware upgradeable through TFTP/FTP/HTTP	Power	
Configuration backup & restore	Supports text configuration file for quick system installation USB port to upload/download configuration and upgrade firmware* by USB dongle Dual image firmware*	Input power	Dual DC input, isolated 16.8VDC~137.5VDC for (WV model)
Physical Ports & System		Power consumption (Typ.)	20 Watts
Connectors	10/100/1000T: 6x ports M12 8-pole X-coded with Auto MDI/MDI-X function USB/Console connector: 1 x M12 8-pole A-coded DIDO : 1 x M12 5-pole A-coded Power Input connector : 1 x M12 4-pole A-coded Serial connector : 2 DB9 SIM card slots : 2 SMA/QMA** connector for LTE: 6 (female)	Physical Characteristic	
Serial Baud Rate	1000Kbps high data rate,250kbps normal for RS232 ; 20Mbps high data rate,250kbps normal for RS422/485	Enclosure	IP 65/54 aluminum case
Serial Data Bits	5, 6, 7, 8	Dimension	178 (W) x 99 (D) x 103 (H) mm
Serial Parity	odd, even, none, mark, space	Weight	1000g
Serial Stop Bits	1, 1.5, 2	Environmental	
RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND	Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
RS-422	Tx+, Tx-, Rx+, Rx-,GND	Operating Temperature	-20°C ~ 75°C (-4°F ~ 167°F) -40°C ~ 75°C (-40°F ~ 167°F) -E model
RS-485 (2-wire)	Data+, Data-,GND	Operating Humidity	5% to 95% Non-condensing
Isolation protection	RS422/485 2.5KV isolation; 8KV contact & 15KV air RS232 8KV contact and 15KV air ESD DIDO 3KV isolation Input power 1.5KVA isolation	Regulatory approvals	
		EMC	FCC Part 15 Class A, EN55032
		EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-4-11
		Stability Testing	EN61373 (Shock & Vibration)
		Railway verification	EN50155*, 50121*,45545
		MTBF	495,724 Hrs (IEC62830 standards)
		Warranty	5 years

*Future Release
**Optional

ORDERING INFORMATION

All standard models are non-conformal coating, optional conformal coating are with -C model name; Optional bypass models are available with -BT model name; QMA connector models are with -Q model name; -40~75C operational models are with -E model name.

- **TMR-5006-1L-2S-WV-65-EUNA.....P/N: 8651-021**
EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 serial ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band; dual isolated 16.8V~137.5VDC; IP65; -20~75C
- **TMR-5006-1L-2S-WV-65-WW.....P/N: 8651-022**
EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 serial RS-232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band; dual isolated 16.8V~137.5VDC; IP65; -20~75C
- **TMR-5006-1L-2S-WV-65-APAC.....P/N: 8651-023**
EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 serial RS-232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band; dual isolated 16.8V~137.5VDC; IP65; -20~75C
- **TMR-5006-1L-2SA-WV-65-EUNA.....P/N: 8651-0211**
EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band ; dual isolated 16.8V~137.5VDC; IP65 ; -20~75C
- **TMR-5006-1L-2SA-WV-65-WW.....P/N: 8651-0221**
EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band ; dual isolated 16.8V~137.5VDC; IP65 ; -20~75C
- **TMR-5006-1L-2SA-WV-65-APAC.....P/N: 8651-0231**
EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band ; dual isolated 16.8V~137.5VDC;

- IP65 ; -20~75C

■ **TMR-5006-1L-2S-WV-54-EUNA.....P/N: 8651-041**
 EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band; dual isolated 16.8V~137.5VDC; IP54; -20~75C
- **TMR-5006-1L-2S-WV-54-WW.....P/N: 8651-042**
 EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band; dual isolated 16.8V~137.5VDC; IP54; -20~75C
- **TMR-5006-1L-2S-WV-54-APAC.....P/N: 8651-043**
 EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band; dual isolated 16.8V~137.5VDC; IP54; -20~75C
- **TMR-5006-1L-2SA-WV-54-EUNA.....P/N: 8651-0411**
 EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band ; dual isolated 16.8V~137.5VDC; IP54 ; -20~75C
- **TMR-5006-1L-2SA-WV-54-WW.....P/N: 8651-0421**
 EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors+ 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band ; dual isolated 16.8V~137.5VDC; IP54 ; -20~75C
- **TMR-5006-1L-2SA-WV-54-APAC.....P/N: 8651-0431**
 EN50155 Multifunction VPN Router + 1 LTE 4G SMA connectors+ 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band ; dual isolated 16.8V~137.5VDC; IP54 ; -20~75C
- **TMR-5006-2L-2S-WV-65-EUNA.....P/N: 8651-024**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 serial ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band; dual isolated 16.8V~137.5VDC; IP65; -20~75C
- **TMR-5006-2L-2S-WV-65-WW.....P/N: 8651-025**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 serial RS-232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band; dual isolated 16.8V~137.5VDC; IP65; -20~75C
- **TMR-5006-2L-2S-WV-65-APAC.....P/N: 8651-026**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 serial RS-232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band; dual isolated 16.8V~137.5VDC; IP65; -20~75C
- **TMR-5006-2L-2SA-WV-65-EUNA.....P/N: 8651-0241**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band ; dual isolated 16.8V~137.5VDC; IP65 ; -20~75C
- **TMR-5006-2L-2SA-WV-65-WW.....P/N: 8651-0251**
 EN50155 Multifunction VPN Router + 2TE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band ; dual isolated 16.8V~137.5VDC; IP65 ; -20~75C
- **TMR-5006-2L-2SA-WV-65-APAC.....P/N: 8651-0261**
 EN50155 Multifunction VPN Router + 2LTE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band ; dual isolated 16.8V~137.5VDC; IP65 ; -20~75C
- **TMR-5006-2L-2S-WV-54-EUNA.....P/N: 8651-044**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band; dual isolated 16.8V~137.5VDC; IP54; -20~75C
- **TMR-5006-2L-2S-WV-54-WW.....P/N: 8651-045**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band; dual isolated 16.8V~137.5VDC; IP54; -20~75C
- **TMR-5006-2L-2S-WV-54-APAC.....P/N: 8651-046**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band; dual isolated 16.8V~137.5VDC; IP54; -20~75C
- **TMR-5006-2L-2SA-WV-54-EUNA.....P/N: 8651-0441**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors + 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; EU and US band ; dual isolated 16.8V~137.5VDC; IP54 ; -20~75C
- **TMR-5006-2L-2SA-WV-54-WW.....P/N: 8651-0451**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors+ 2 isolated serial RS422/485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; Worldwide band ; dual isolated 16.8V~137.5VDC; IP54 ; -20~75C
- **TMR-5006-2L-2SA-WV-54-APAC.....P/N: 8651-0461**
 EN50155 Multifunction VPN Router + 2 LTE 4G SMA connectors+ 2 isolated serial RS422/485 ports + 6 Gigabit X-coded

Ethernet managed switch for Load Balancing**, VPN, Protocol Gateway; APAC band ; dual isolated 16.8V~137.5VDC;
IP54 ; -20~75C

EMMC Flash Storage

- **8G**.....P/N: **8850-113**
- **16G**.....P/N: **8850-114**
- **32G**.....P/N: **8850-115**
- Software License**
- **LOAD BALANCING Basic Package**.....P/N: **9000-101**
- **LOAD BALANCING Full Package**.....P/N: **9000-102**

OPTIONAL ACCESSORIES

LTE Antenna

- **ANT11000041** 791-960/1710~2175/2500~2750MHZ, SMA plug, EU
- **ANT11000042** 754-960/1710~2175MHZ, SMA plug, US

Lantech Communications Global Inc.

www.lantechcom.tw
info@lantechcom.tw

© 2018 Copyright Lantech Communications Global Inc. all rights reserved.
The revise authority rights of product specifications belong to Lantech Communications Global Inc.
Lantech may make changes to specification and product descriptions at anytime, without notice.