


LantechTM

2020 PRODUCT GUIDE



CASE REFERENCES



CONTENTS

Industrial Solutions

On-board Networking Switches for TCMS Communications	1
On-board / Trackside Networking Multi-function Routers	3
Intelligent Transportation System	5
Autonomous Car	7
Bus Communications System	8
Building Automation	9
Factory Automation	9
Process Control	9

Hardened Ethernet Connections

Feature Highlights of Multi-function Routers	11
How To Find A Right Model?	14
4G LTE + Wi-Fi Multifunction Routers	15
4G LTE Multifunction Routers	15
Wi-Fi Multifunction Routers	15
EN50155 NAT Routers	15

Feature Highlights of Hardened & Rolling Stock Ethernet Switches	17
Enhanced ITU G.8032 Ring	19
OS Platform's Comparison	20
EN50155 10G Uplinks Managed Ethernet Switches	21
EN50155 2.5G Uplinks Managed Ethernet Switches	22
EN50155 Rackmount Ethernet Switches	23
EN50155 Giga Uplinks Managed Ethernet Switches	23
EN50155 Unmanaged Ethernet Switches	24

ABOUT LANTECH

With a long background in IP Ethernet products, Lantech brings the best network solutions for industrial and IP networks to the marketplace. The Lantech group is devoted to providing end user benefits & feature rich innovative high-quality networking solutions. We provide outstanding service and support to our world-wide partners & distribution network. Lantech provides high quality products with customer-focused services from our sales offices located in Taiwan, Germany, UK and Singapore.

Our core values are based on our firmware modularity development to meet with special requirement of projects as well as the continuous improvement of hardware to cope with different levels of certificate and criteria for various harden applications including rollingstock railway, trackside, vehicle, transportation, maritime, offshore, power substation, industrial surveillance. PoE(power over Ethernet) is one of key advantage solution which Lantech is good at DC-DC conversion built-in the switch and router that could have greater PoE budget and wider input voltage range.

Lantech products are successfully deployed around the world and used in all types of applications, including bus system in Spain, tram system in Finland, train in France and Germany, outdoor wireless surveillance system in Malaysia, military truck system in Vietnam, traffic networks in the UK and city surveillance system in Romania, etc.

As an IRIS-certified company, Lantech ensures that the quality of our products and services meets the high standards required by our customers worldwide and are suitable for use in the rail industry.

Quality Policy

Technical Innovation
Sustainable Improvements
Customer Satisfaction
Grow Responsibly with Suppliers

Safety Policy

Create Safety Awareness
Implement Safety Training
Guarantee Safe Operations
Provide Safe Products



*Industrial-grade products

Ethernet Connections

Industrial L3/10G (PoE) Ethernet Switches	25
Industrial Managed (PoE) Ethernet Switches	26
Industrial Unmanaged (PoE) Ethernet Switches	27
Industrial IEC 61850-3 Ethernet Switches	28
Industrial DNV Type Ethernet Switches	29
Industrial Hazardous Ethernet Switches	30
Industrial Entry Ethernet Switches	31
Industrial Converter Series	31

Serial Devices	32
Central Managed Ethernet Switches	32
PoE Series	32
Fiber Converters	33
Lantech Product Naming Rule	33


Accessories

Multifunction Antenna	34
Cellular Antenna	34
Wi-Fi Antenna	34
Antenna Base	34
SFP (Mini-GBIC)	35
Bracket	35
Power Supply	36
Cable	36
Connector	36

WiFi is not available



On-board Networking Switches for TCMS Communications



Optional Railway Network Address Table (R-NAT) for OS4 models


Smart Bypass Protection

EN 50155:2017, EN 50121-4, EN 55032 and EN45545-2

Wide Voltage Input 16.8~137.5VDC w/ Isolation

Inrush Current Limit

Up to 80W PoE w/PoE & System Isolation



Train Control Network (E-TCN) — ETB (x2) — ECN

Train Communication and Diagnostics Network (E-TCDN) — ETB (x2) — ECN

Discrete Train-line Network —

Product Selection



TPGS-R6616XFT

16 10/100/1000T PoE at + 4 10G copper
+ 2 10G Q-ODC fiber OS4 EN50155
Managed Switch



TPES-L6424XFT

24 10/100TX (PoE at) + 2 10G copper +
2 10G Q-ODC fiber OS3 EN50155
Managed Switch



TPGS-L6416XFT

8 10/100/1000T PoE at + L2+ EN50155
Managed Switch



TPGS-L6408XFT


8 10/100TX PoE at + 4 10/100/1000T
L2+ EN50155 Managed Switch

Industrial Solutions

Hardened Ethernet
Connections

Ethernet
Connections

Accessories



On-board / Trackside Networking Multi-function Routers



IP Phone



Train Sub-communication Networks

Lorem ipsum dolor sit amet,
consectetur adipiscing elit,
sed do eiusmod tempor



CCTV



Wi-Fi Hotspot



PIS


Features at a glance Lantech Multi-function Routers


Wi-Fi

- Wireless Roaming with 802.11k & v
- Advanced security & 16 SSIDs
- IEEE 802.11ac Dual Band Operation
- 802.11s Wireless Mesh Network

Software

- Multisite VPN, OpenVPN and Firewall
- Managed Switch Built-in
- Load Balancing





BEST FOR TRACKSIDE

802.11s
Wireless Mesh Network

MESH

&
Fiber Connection

Product Selection



TWMR-5208MGF

EN50155 Multifunction VPN Router w/1x WiFi 11ac
+ 1 LTE 4G + 8 GigaT + 2 1G/2.5G Fiber + 2 copper WAN



TWMR-5006

EN50155 Multifunction VPN Router
w/1x WiFi 11ac + 1 LTE 4G + 2 serial ports
+ 6 Gigabit X-coded Ethernet Switch



IWMR-3204DF

Industrial Multifunction VPN Router w/up to
2x WiFi 11ac + up to 2 LTE 4G + 2 serial ports
+ 4 Gigabit Ethernet + 2 Dual Speed SFP Switch

LTE

Dual Concurrent LTE Design 4G/3G
eSIM Chip Built-in

Hardware

Galvanic Isolation, Wide Input Voltage
USB Port for Configuration
Optional EMMC Flash Storage**
Ignition Sensing
Serial Ports: Modbus Gateway


**Optional

Industrial Solutions


Hardened Ethernet
Connections

Ethernet
Connections

Accessories




Intelligent Transportation System



✓ Parking Guidance Info

✓ Real-time Parking App



✓ Surveillance



✓ Traffic Light Control System

✓ Traffic Analysis

✓ Traffic Monitoring



Product Selection



IWMR-3204DF

Industrial Multifunction VPN Router
w/up to 2x WiFi 11ac + up to 2 LTE 4G
+ 2 serial ports + 4 Gigabit Ethernet
+ 2 Dual Speed SFP Switch




IPGS-3408GSFP

8 10/100/1000T PoE at
+ 4 1000M SFP L2+
Industrial Managed
Ethernet Switch

✓ RFID Tolling System

✓ Traffic Analysis

✓ Traffic Monitoring



Industrial Solutions


Hardened Ethernet
Connections

Ethernet
Connections

Accessories

Autonomous Car

"Data transmission between 4K/8K camera, 360 degree camera, sensor, radar, GPS and inertial measurement units"



Lantech DIN-Rail 10G Uplinks Managed Ethernet Switches

- 4 x 10G Uplinks Fiber or Copper*
- Optional L3/L3 lite Capacity
- USB Port for Backup and Configuration
- Built-in Power Converter (12VDC input / 24VDC input)
- Feed 30W Power – 802.3at Standard (PoE models)
- Configurable Power Budget (240W@48V; 120W@24V; 80W@12V)
- PoE Detection and Scheduling
- Built-in Environmental Monitoring
- Wide range operation temperature: -40~75°C/-40~167°F
- Fan-less design

*10G copper SFP: only used from 18V~57VDC power input, maximum two ports

Lantech EN50155 10G Uplinks Managed Ethernet Switches

- IP54/21-rated Aluminum Housing
- Inrush Current Limit
- L2+ or L3 Lite Management
- EN 50155 / EN 45545-2 Certified
- Wide Voltage 16.8~137.5VDC Isolated Input w/ PoE 80W Budget
- PoE Detection and Scheduling
- Built-in Environmental Monitoring
- Wide range operation temperature: -40~75°C/-40~167°F
- Fan-less design

Bus Communications System



Industrial Solutions

Hardened Ethernet Connections

Ethernet Connections

Accessories

Lantech Industrial 7-in-1 Multi-function Routers

- Wi-Fi 802.11ac
- Storage
- Gateway
- Managed Switch
- LTE
- PoE
- VPN



Lantech E-Marking Certified Ethernet Switches

E4



I(P)ES-0005B
5 10/100TX
(PoE at) EN50155
Unmanaged Switch



I(P)ES-0008B
8 10/100TX
(PoE at) EN50155
Unmanaged Switch

E13



IES-0016
16 10/100TX
Industrial
Unmanaged Switch



I(P)GS-0008B
8 10/100/1000T
(PoE) Industrial
Unmanaged Ethernet Switch



I(P)ES-0008B
8 10/100TX
(PoE) Industrial
Unmanaged Ethernet Switch


Lantech ITxPT Compliant Ethernet Switches




T(P)GS-0008CA
8 10/100/1000T
(PoE at) EN50155
Unmanaged Switch





T(P)ES-0008CA
8 10/100TX
(PoE at) EN50155
Unmanaged Switch




Building Automation



Factory Automation



Process Control



Challenges

Historically, building owners in the market for a new Building Management Systems (BMS) have been forced to choose between one of several proprietary equipment manufacturers. Normally BMS equipment is fitted in compact wall mounted control cabinets that are distributed around the building, with most devices being DIN Rail mounted.

Our Solutions

The use of TCP/IP for BMS system communications has brought about increased choice in selecting products from different vendors in the same BMS system and reducing the associated cabling and network hardware costs. For cable runs which exceed the 100 meter limitation of Cat5e or for links between different buildings, a fiber optic link is the ideal solution.

IES-2208CA

8 10/100TX + 2 10/100/1000T/
Dual Speed SFP Combo
Industrial Managed Switch



- 100M/1000M Dual Speed SFP Fiber
- Pro-Ring 2se covers Single-Ring Topology
- Wide operating temperature range from -40°C to 75°C

Industrial Solutions

Hardened Ethernet Connections

Challenges

The most dynamic and challenging part for factory automation floor network is redundancy and real-time. Factory automation needs to be absolutely accurate because any interruption or delay could result in huge amount of lost, especially when the operation is non-stop, 7/24/365. On the other hand, to satisfy the rapid changing industry environment, manufacturing process must have high flexibility than before.

Our Solutions

Based on IP protocol, managers are able to control equipments and transmit data to SCADA, where connects with database and then generate statistic data for monitoring the operating status. As the equipments are all utilizing IP protocol and connect to the Ethernet, it's easier to integrate and change configuration through Internet. By collocating with Ethernet switches, managers are able to monitor the status, detect the failure, and solve the problem immediately.

IES-3408GSFP

4 1000FX + 8 10/100TX
L2+ Managed Ethernet Switch



- Wide range dual DC powered input with galvanic isolation
- Enhanced G.8032 ring protection
- Wide operating temperature range from -40°C to 70°C

Ethernet Connections

Accessories

Challenges

Water treatment process is essential for modern life to make water more acceptable and eliminating bad residues existing in many public sanitation systems then to return water back into natural environment without ecological impacts for the use of drinking water, industrial process, medical, hotel process and others.

Our Solutions

Using the industrial Ethernet network is the most convenient and reliable solution for water treatment system to connect with SCADA, PLC, water sensors, water bumps etc. Since the water treatment plant might cover huge floor space, the long transmission distance becomes one of the major considerations.

IGS-3204MGSPF

2 1G/2.5GSFP + 4 10/100TX
L2+ Managed Ethernet Switch



- Slim design
- Up to 2.5G Speed SFP Fiber
- Enhanced ITU G.8032 Ring
- USB port for backup & restore
- Wide operating temperature range from -40°C to 70°C

Why Choosing Lantech?

FEATURE HIGHLIGHTS OF MUL

01

7-in-1 Multifunction



03

Highly Redundancy

LTE & WiFi client redundancy



Wi-Fi client & Wi-Fi client redundancy



LTE & LTE redundancy



LTE & WAN port redundancy



5-in-1 Wireless Modes



02

Up to 2 WAN + 4 LAN Ports



04

SIM Redundancy

2 SIM cards failover per LTE module



40 seconds


2 active LTE modules failover (with 2 SIMs redundancy in each module)



5 seconds

05

802.11s Wireless Mesh Network



06

LAN Ethernet Ring Redundancy

on fiber




or on copper



07

TI-FUNCTION ROUTERS

08 WAN-WAN Redundancy



09 DDOS & Firewall

Lantech's DDOS protection can effectively block all kinds of DDoS attacks

- ✓ UDP Flood
- ✓ TCP SYN Flood
- ✓ ICMP Flood
- ✓ Ping of death
- ✓ Distributed HTTP flood
- ✓ BotNet (Zombie Network)
- ✓ Application level floods




10

Load balancing on WAN ports


Fixed

Manually route by traffic type through fixed WAN link.




Priority

Routes connections through preferred WAN link while others stand-by. Sequentially activating other links if overflow occurs.




Fail Over

Routes connections through preferred WAN link while others stand-by. Sequentially activating another link if preferred link fails.



Weighted Round-Robin

Even distribution of the traffic over all working WAN links in circular order according to the specified weights.




Custom Route

Routing through the selected WAN links for each specific traffic, ex: TCP/UDP port number and IP address.



Work as DHCP option 82 relay



Easy to control specific dynamic IPs and avoid from IP confliction

11

QoS on WAN

By port: Filter by applications
By protocol: Filter by protocol




12

Full VPN support

- OpenVPN
- IPSec
- Multi-site VPN
- L2TP over IPSec
- L2 over GRE
- IPGRE MDVPN

13

Customized controller software integrated with router



14

15

Built-in Managed Switch Function



- ✓ Port Management
- ✓ QoS
- ✓ VLAN
- ✓ Multicast
- ✓ Redundant Protection
- ✓ Security

No need to purchase extra switches for a small network

Support Dynamic Route



Most competitors only support RIP

17

16

Supports IPv6



- ✓ Resolve IP Address space exhaustion
- ✓ Elimination of NAT
- ✓ Makes routing more efficient.
- ✓ Simplified Network Configuration and easier to management

Integrated PoE Functions



PoE Detection

Monitoring power consumption, voltage, current and temperature in real time

PoE Schedule

Customize the schedule to ON/OFF PoE

Power Budget Management

18

Ignition sensing on 3000 series to extend the operation time when engine is off



Engine is off



Extended operation time



Router shut down

19

Optional eSIM (only 5008 series)



22

Double isolation design to minimize the risk of surge, EFT at input, PoE and serial ports



Surge

EFT

Input


PoE

Serial

20

802.11AC 3Tx3R Wi-Fi

Multi-channel 3Tx3R Wi-Fi 11ac for maximum communication bandwidth



transmitters receivers

433Mbps x3 = 1.3Gbps

21

23

Optional EMMC storage inside router



8GB

16GB

32GB

LTE Status Timeline

To check the LTE status at a glance



24

Superior LTE Performance

Reliable brand

LTE module is powered by



High compatibility

- APAC model for Asia & Oceania
- EUNA model for Europe & North America
- WW model for worldwide

Fast speed

Cat 4 = 150 Mbps

- Downlink (Cat 6): FDD: 300 Mbps TDD: 222 Mbps
- Uplink (Cat 6): FDD: 50 Mbps TDD: 26 Mbps

25

How To Find A Right Model? WIFI, MOBILE, OR BOTH?

**Wi-Fi
+
LTE**

**LTE
Only**

**Wi-Fi
Only**

Model Name
IPW**M**R-3XXX
IW**M**R-3XXX
TPW**M**R-5XXX
TW**M**R-5XXX

Model Name
IP**M**R-3XXX
I**M**R-3XXX
TP**M**R-5XXX
T**M**R-5XXX

Model Name
IPWAP-3XXX
IWAP-3XXX
TPWAP-5XXX
TWAP-5XXX

Multifunction Wi-Fi + LTE Routers

Multifunction LTE Mobile Routers

Multifunction Wi-Fi Routers

	5000 Series	3000 Series	5000 Series	3000 Series	5000 Series	3000 Series
Aluminum case	●	-	●	-	●	-
SIM slots	Up to 4	Up to 4	Up to 4	Up to 4	-	-
SMA antenna connectors	Up to 9	Up to 7	Up to 9	Up to 7	Up to 9	Up to 7
802.11ac/a/b/g/n WiFi	●	●	-	-	●	●
Power inputs	16.8~137.5VDC (WV model)	9~60VDC (24V model)	16.8~137.5VDC (WV model)	9~60VDC (24V model)	16.8~137.5VDC (WV model)	9~60VDC (24V model)
WiFi WMM	●	●	-	-	●	●
Ignition sensing	-	●	-	●	-	●

Industrial Solutions

Hardened Ethernet
Connections

Ethernet
Connections

Accessories

Product Line-ups

4G LTE + Wi-Fi Multifunction Routers



T(P)WMR-5208MGF

EN50155 Multifunction VPN Router w/1 WiFi 11ac + 1 LTE 4G + 8 GigaT + 2 1G/2.5G Fiber



T(P)WMR-5208MGT

EN50155 Multifunction VPN Router w/1 WiFi 11ac + 1 LTE 4G + 8 GigaT + 2 1G/2.5G Copper



T(P)WMR-5008

EN50155 Multifunction VPN Router w/1 WiFi 11ac + 1 LTE 4G + 8 GigaT Ethernet + 4 serial ports



T(P)WMR-5006

EN50155 Multifunction VPN Router w/1 WiFi 11ac + 1 LTE 4G + 2 serial ports + 6 GigaT



T(P)WMR-5004

EN50155 Multifunction VPN Router w/1 WiFi 11ac + 1 LTE 4G + 2 serial ports + 4 GigaT + 2WAN



TWMR-5002

EN50155 Multifunction VPN Router w/1 WiFi 11ac + 1 LTE 4G + 2 serial ports + 2 GigaT (incl.1 PD)



4G LTE Multifunction Routers



T(P)MR-5208MGF

EN50155 Multifunction VPN Router w/2 LTE 4G + 8 GigaT + 2 1G/2.5G Fiber



T(P)MR-5208MGT

EN50155 Multifunction VPN Router w/2 LTE 4G + 8 GigaT + 2 1G/2.5G Copper



T(P)MR-5008

EN50155 Multifunction VPN Router w/2 LTE 4G + 8 GigaT Ethernet + 4 serial ports



T(P)MR-5006

EN50155 Multifunction VPN Router w/2 LTE 4G + 2 serial ports + 6 GigaT



T(P)MR-5004

EN50155 Multifunction VPN Router w/2 LTE 4G + 2 serial ports + 4 GigaT + 2WAN



TMR-5002

EN50155 Multifunction VPN Router w/2 LTE 4G + 2 serial ports + 2 GigaT (incl.1 PD)



Wi-Fi Multifunction Routers



T(P)WAP-5208MGF

EN50155 Multifunction VPN Router w/2 WiFi 11ac + 8 GigaT + 2 1G/2.5G Fiber



T(P)WAP-5208MGT

EN50155 Multifunction VPN Router w/2 WiFi 11ac + 8 GigaT + 2 1G/2.5G Copper



T(P)WAP-5008

EN50155 Multifunction VPN Router w/2 WiFi 11ac + 8 GigaT Ethernet + 4 serial ports



T(P)WAP-5006

EN50155 Multifunction VPN Router w/2 WiFi 11ac + 2 serial ports + 6 GigaT



T(P)WAP-5004

EN50155 Multifunction VPN Router w/2 WiFi 11ac + 2 serial ports + 4 GigaT + 2WAN



TWAP-5002

EN50155 Multifunction VPN Router w/2 WiFi 11ac + 2 serial ports + 2 GigaT (incl.1 PD)



EN50155 NAT Routers



T(P)GR-5208MGF-2WAN

8 10/100/1000T + 2 1G/2.5G Q-ODC Fiber + 2 1G/2.5G WAN EN50155 L2+ Managed Ethernet Router



T(P)GR-5208MGT-2WAN

8 10/100/1000T + 2 1G/2.5G Copper + 2 1G/2.5G WAN EN50155 L2+ Managed Ethernet Router



Model name (P) = PoE model

**I(P)WMR-3204DF**

Industrial Multifunction VPN
Router w/up to 2 WiFi 11ac
+ up to 2 LTE 4G + 2 serial
ports + 4 GigaT + 2
Dual Speed SFP

**I(P)WMR-3004DF**

Industrial Multifunction VPN
Router w/up to 2 WiFi 11ac
+ up to 2 LTE 4G + 2 serial
ports + 4 GigaT + 2
Dual Speed SFP WAN

**I(P)WMR-3006**

Industrial Multifunction VPN
Router w/up to 2 WiFi 11ac
+ up to 2 LTE 4G + 2 serial
ports + 6 GigaT

**I(P)WMR-3004**

Industrial Multifunction VPN
Router w/up to 2 WiFi 11ac
+ up to 2 LTE 4G + 2 serial
ports + 4 GigaT + 2WAN

**IWMR-3002**

Industrial Multifunction VPN
Router w/up to 2 WiFi 11ac
+ up to 2 LTE 4G
+ 2/4 serial ports + 2 GigaT

**I(P)MR-3204DF**

Industrial Multifunction VPN
Router w/2 LTE 4G + 2 serial
ports + 4 GigaT + 2
Dual Speed SFP

**I(P)MR-3004DF**

Industrial Multifunction VPN
Router w/2 LTE 4G + 2 serial
ports + 4 GigaT + 2
Dual Speed SFP WAN

**I(P)MR-3006**

Industrial Multifunction VPN
Router w/2 LTE 4G +
2 serial ports + 6 GigaT

**I(P)MR-3004**

Industrial Multifunction VPN
Router w/2 LTE 4G +
2 serial ports + 4 GigaT
+ 2WAN

**IMR-3002**

Industrial Multifunction VPN
Router w/2 LTE 4G +
2/4 serial ports
+ 2 GigaT

**I(P)WAP-3204DF**

Industrial Multifunction VPN
Router w/2 WiFi 11ac +
2 serial ports +
4 GigaT + 2 Dual Speed SFP

**I(P)WAP-3004DF**

Industrial Multifunction VPN
Router w/2 WiFi 11ac +
2 serial ports +
4 GigaT + 2 Dual Speed SFP
WAN

**I(P)WAP-3006**

Industrial Multifunction VPN
Router w/2 WiFi 11ac +
2 serial ports + 6 GigaT

**I(P)WAP-3004**

Industrial Multifunction VPN
Router w/2 WiFi 11ac +
2 serial ports
+ 4 GigaT + 2WAN

**IWAP-3002**

Industrial Multifunction VPN
Router w/2 WiFi 11ac +
2/4 serial
ports + 2 GigaT

**IWAP-3003**

Industrial Multifunction VPN
Router w/2 WiFi 11ac +
2/4 serial
ports + 3 GigaT



Learn more about Lantech multifunction routers



5000 Series Routers



3000 Series Routers

Why Choosing Lantech?

FEATURE HIGHLIGHTS OF HARDENED &

01

Optional Layer 3 Lite (L3L)

Layer
3 Lite

OS4 Platform
OS3 Platform

1. Inter-VLAN Routing

Route traffic between different VLAN by implementing a switch with routing function in the network.


2. Router-on-a-stick

A type of routing configuration in which a single physical interface set as VLAN trunk port manages traffic between multiple VLANs from edge site.


3. VRRP

Provides automatic assignment of available VLAN gateways to participating hosts and increases the availability and reliability of VLAN routing paths via automatic default gateway selections on different VLAN groups.


1. Inter-VLAN Routing



2. Router-on-a-stick



3. VRRP



Optional Layer 3

Layer
3

1. OSPF

Open Shortest Path First (OSPF) protocol is an Interior Gateway Protocol used to distribute routing information within a single Autonomous System.

2. RIP

Routing Information Protocol (RIP) is a dynamic routing protocol which uses hop count as a routing metric to find the best path between the source and the destination network.

3. PIM

Protocol-Independent Multicast (PIM) is a family of multicast routing protocols for Internet Protocol (IP) networks that provide one-to-many and many-to-many distribution of data over a LAN, WAN or Internet.

4. DVMRP

Distance Vector Multicast Routing Protocol (DVMRP) is a routing protocol used to share information between routers to facilitate the transportation of IP multicast packets among networks.

OS4 Platform
OS3 Platform

02


Software Advantage – Layer 2+

OS4 Platform
OS3 Platform


1. PXE
2. Protocol based VLAN
3. IPv6 Multicast
4. Subnet based VLAN

03


1. PXE




2. Protocol-based VLAN



3. IPv6 Multicast




4. Subnet-based VLAN



ROLLING STOCK ETHERNET SWITCHES

Optional TBN (IEC 61375-2-5) & built-in ECN (IEC 61375-3-4)

Backbone of train network which is responsible to exchange the data from each consist




OS4 Platform
OS3 Platform

04

Optional R-NAT (IEC 61375-2-5)

If ED#53 will communicate with ED#21, it doesn't need to know the IP address of ED#21 but just need to know the IP address of TBN which is responsible to build physical connection with ED#21.



OS4 Platform

05

Real-time Environmental Monitoring



Real input voltage in routers & OS3/OS4 Ethernet switches



OS4 Platform
OS3 Platform

06

Wide Voltage (Isolated)
16.8~137.5VDC Power Input
(EN50155 Series)

Built-in Power Converter
12/24VDC boost up to 48VDC
(Industrial Series)

**WIDE
Voltage**
+Isolation

**12V
booster
48V**

07

Compliance to Various Standards for Different Applications



Rolling Stocks
• EN 50155:2017
• EN 50121-4
• EN 55032
• EN 45545-2

Vehicles
• E-Marking
• ITxPT

Power Substations
• IEC 61850-3
• IEEE 1613

Maritime
• DNV

Industrial & Outdoor
• IP30 rated to IP67 rated

08

Integrated PoE Functions



PoE Detection

Monitoring power consumption, voltage, current and temperature in real time

PoE Schedule

Customize the schedule to ON/OFF PoE

PoE Budget Management

09

Smart Bypass Protection (Optional)

The bypass relay is set to bypass the switch to the next one when power is off or CPU hanged to prevent network disruption.



10

10GbE Connectivity - To Fulfill Huge Bandwidth Requirement



11

Inrush Current Protection



The inrush current on initial power up can be limited lower than 10 x nominal current and for less than 1ms.

12

USB port to upload & download the configuration file




13

Enhanced ITU G.8032 Ring

OS4 Platform
OS3 Platform
OS2 Platform
OS1 Platform


Established by ITU (International Telecommunication Unit), the G.8032 protocol is compatible with Ethernet standard and has been supported by many major Ethernet system providers. With our long background in IP Ethernet industry, Lantech is proud to present our enhanced ITU G.8032 ring which covers multicast & data recovery.



Lantech G.8032 ring has basic, auto, enhanced, multi-train mode.

Basic	Compliant with 3rd party ERPS switch, recovery time <100ms
Auto	Single ring auto-select each role
Enhanced	Support data/ multicast recovery <20ms in single ring
Multi-Train	Support auto dynamic coupling

Enhanced Ring for Multicast Recovery



What's the difference?

OS PLATFORM's COMPARISON

**Complete
management
levels, L2+, L3 Lite**, L3***

OS4 Platform	OS3 Platform	OS2 Platform	OS1 Platform
L2+ Dual image L3L** L3** TBN** ECN Hardware-NAT**	L2+ Dual image L3L** L3** TBN** ECN	L2+ Dual image	L2+

	Layer 3 Lite (L3L)	Layer 2 +			Layer 2
		OS4/OS3	OS2	OS1	2000 series
TTDP (IEC 61375)	•				
R-NAT*	•				
IP based port	•				
VLAN routing	•				
VRRP	•				
Static Unicast Routing	•				
DHCP pool with per VLAN	•				
IP Source Guard	•				
MRP	•	•			
Protocol Based	•	•			
Subnet Based	•	•			
MLD Snooping	•	•			
Port Monitoring	•	•			
PXE application	•	•			
IP v6 DHCP Server (Basic)	•	•			
Dual Image	•	•	•		
ARP inspection	•	•		•	
BPDU Guard	•	•		•	
QinQ	•	•		•	
Remote admin (limitation of accessing way)	•	•	•	•	
GVRP	•	•	•	•	
SSL	•	•	•	•	
Login Security (TACACS+)	•	•	•	•	
Login Security (RADIUS)	•	•	•	•	
Dual Homing	•	•	•	•	
SSH	•	•	•	•	
CDP	•	•	•	•	
Topology View	•	•	•	•	
Environment Monitoring	•	•	•	•	
MSTP	•	•	•	•	
Loop Protection	•	•	•	•	
IGMP router port	•	•	•	•	
GMRP	•	•	•	•	
VLAN based QoS	•	•	•	•	
MAC based DHCP	•	•	•	•	
Option82 DHCP Relay	•	•	•	•	
Option 12/42/66	•	•	option 66 only	option 66 only	
DHCP Snooping	•	•	•	•	
Digital Input/Output	•	•	•	•	
Triggered by event of environment	•	•	•	•	
Triggered by event of SFP DDM	•	•	•	•	
Ping	•	•	•	•	
ARP	•	•	•	•	
QoS under 61375-3-4	•	•	•	•	
Proprietary redundant protocol	ITU-Ring Enhance mode	ITU-Ring Enhance mode	ITU-Ring Enhance mode	ITU-Ring Enhance mode	ProRing2se
ACL	Ingress only	Ingress only	Ingress Only	•	•
SNMP Trap	•	•	•	•	V1/V2c
Firmware upgrading	WEB/TFTP/FTP	WEB/TFTP/FTP	WEB/TFTP/FTP	WEB/TFTP/FTP	WEB/TFTP
Configuration file import/export	WEB/TFTP/FTP	WEB/TFTP/FTP	WEB/TFTP/FTP	WEB/TFTP/FTP	WEB/TFTP
G.8032 standard				•	
Auto Provision				•	

* Future release
** Optional
***Spec may vary by model

Industrial Solutions

Hardened Ethernet
Connections

Ethernet
Connections

Accessories

EN50155 10G Uplinks Managed Ethernet Switches

OS4 Platform



T(P)GS-R6616XFT
16 10/100/1000T (PoE at) +
4 10G copper + 2 10G Q-ODC fiber
EN50155 OS4 Managed Switch



T(P)GS-R6616XT
16 10/100/1000T (PoE at)
+ 6 10G copper
EN50155 OS4 Managed Switch



T(P)GS-R6416XFT
16 10/100/1000T (PoE at)
+ 2 10G copper + 2 10G Q-ODC
Fiber EN50155 OS4 Managed Switch



T(P)GS-R6416XT
16 10/100/1000T (PoE at)
+ 4 10G copper
EN50155 OS4 Managed Switch



T(P)GS-R6608XFT
8 10/100/1000T (PoE at) +
4 10G copper + 2 10G Q-ODC fiber
EN50155 OS4 Managed Switch



T(P)GS-R6608XT
8 10/100/1000T (PoE at)
+ 6 10G copper
EN50155 OS4 Managed Switch



T(P)GS-R6408XFT
8 10/100/1000T (PoE at) +
2 10G copper + 2 10G Q-ODC Fiber
EN50155 OS4 Managed Switch



T(P)GS-R6408XT
8 10/100/1000T (PoE at)
+ 4 10G copper
EN50155 OS4 Managed Switch



OS3 Platform



T(P)ES-R6616XFT
16 10/100TX (PoE at) +
4 10G copper + 2 10G Q-ODC fiber
EN50155 OS4 Managed Switch



T(P)ES-R6616XT
16 10/100/1000T (PoE at)
+ 6 10G copper
EN50155 OS4 Managed Switch



T(P)GS-L6416XFT
16 10/100/1000T (PoE at)+
2 10G Copper + 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch



T(P)GS-L6416XT
16 10/100/1000T (PoE at)
+ 4 10G Copper
EN50155 OS3 Managed Switch



T(P)GS-L6408XFT
8 10/100/1000T (PoE at) +
2 10G Copper + 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch



T(P)GS-L6408XT
8 10/100/1000T (PoE at)
+ 2 10G Copper
EN50155 OS3 Managed Switch



T(P)GS-L6216XT
16 10/100/1000T (PoE at)
+ 2 10G Copper
EN50155 OS3 Managed Switch



T(P)GS-L6216XF
16 10/100/1000T (PoE at)
+ 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch




T(P)GS-L6208XT
8 10/100/1000T (PoE at)
+ 2 10G Copper
EN50155 OS3 Managed Switch




T(P)GS-L6208XF
8 10/100/1000T (PoE at)
+ 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch




T(P)ES-L6424XFT
24 10/100TX (PoE at) +
2 10G copper + 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch



T(P)ES-L6424XT
24 10/100TX (PoE at)
+ 4 10G copper
EN50155 OS3 Managed Switch



T(P)ES-L6416XFT
16 10/100TX (PoE at)+
2 10G Copper + 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch



T(P)ES-L6416XT
16 10/100TX (PoE at)
+ 4 10G Copper
EN50155 OS3 Managed Switch




T(P)ES-L6408XFT
8 10/100TX (PoE at) +
2 10G Copper + 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch



T(P)ES-L6408XT
8 10/100TX (PoE at)
+ 4 10G Copper
EN50155 OS3 Managed Switch



T(P)ES-L6216XT
16 10/100TX (PoE at)
+ 2 10G copper
EN50155 OS3 Managed Switch



T(P)ES-L6216XF
16 10/100TX (PoE at)
+ 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch



T(P)ES-L6208XT
8 10/100TX (PoE at)
+ 2 10G copper
EN50155 OS3 Managed Switch



T(P)ES-L6208XF
8 10/100TX (PoE at)
+ 2 10G Q-ODC fiber
EN50155 OS3 Managed Switch



Model name (P) = PoE model

Learn more



EN50155 2.5G Uplinks Managed Ethernet Switches

OS4 Platform

 T(P)GS-R5616MGFT 16 10/100/1000T (PoE at) + 4 1G/2.5G copper + 2 1G/2.5G Q-ODC fiber EN50155 OS4 Managed Switch 6 2.5G 16 GT 16 PoE USB	 T(P)GS-R5616MGT 16 10/100/1000T (PoE at) + 6 1G/2.5G copper EN50155 OS4 Managed Switch 6 2.5G 16 GT 16 PoE USB	 T(P)GS-R5416MGFT 16 10/100/1000T (PoE at) + 2 1G/2.5G copper + 2 1G/2.5G Q-ODC Fiber EN50155 OS4 Managed Switch 4 2.5G 16 GT 16 PoE USB	 T(P)GS-R5416MGT 16 10/100/1000T (PoE at) + 4 1G/2.5G copper EN50155 OS4 Managed Switch 4 2.5G 16 GT 16 PoE USB
 T(P)GS-R5608MGFT 8 10/100/1000T (PoE at) + 4 1G/2.5G copper + 2 1G/2.5G Q-ODC fiber EN50155 OS4 Managed Switch 6 2.5G 8 GT 10 PoE USB	 T(P)GS-R5608MGT 8 10/100/1000T (PoE at) + 6 1G/2.5G copper EN50155 OS4 Managed Switch 6 2.5G 8 GT 10 PoE USB	 T(P)GS-R5408MGFT 8 10/100/1000T (PoE at) + 2 1G/2.5G copper + 2 1G/2.5G Q-ODC Fiber EN50155 OS4 Managed Switch 4 2.5G 8 GT 10 PoE USB	 T(P)GS-R5408MGT 8 10/100/1000T (PoE at) + 4 1G/2.5G copper EN50155 OS4 Managed Switch 4 2.5G 8 GT 10 PoE USB
 T(P)ES-R5616MGFT 16 10/100TX (PoE at) + 4 1G/2.5G copper + 2 1G/2.5G Q-ODC fiber EN50155 OS4 Managed Switch 6 2.5G 16 TX 16 PoE USB	 T(P)ES-R5616MGT 16 10/100/1000T (PoE at) + 6 1G/2.5G copper EN50155 OS4 Managed Switch 6 2.5G 16 TX 16 PoE USB	OS3 Platform	
		 T(P)GS-L5416MGFT 16 10/100/1000T (PoE at) + 2 1G/2.5G Copper + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 4 2.5G 16 GT 16 PoE USB	 T(P)GS-L5416MGT 16 10/100/1000T (PoE at) + 4 1G/2.5G Copper EN50155 OS3 Managed Switch 4 2.5G 16 GT 16 PoE USB

 T(P)GS-L5408MGFT 8 10/100/1000T (PoE at) + 2 1G/2.5G Copper + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 4 2.5G 8 GT 8 PoE USB	 T(P)GS-L5408MGT 8 10/100/1000T (PoE at) + 2 1G/2.5G Copper EN50155 OS3 Managed Switch 4 2.5G 8 GT 8 PoE USB	 T(P)GS-L5216MGT 16 10/100/1000T (PoE at) + 2 1G/2.5G Copper EN50155 OS3 Managed Switch 2 2.5G 16 GT 16 PoE USB	 T(P)GS-L5216MGF 16 10/100/1000T (PoE at) + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 2 2.5G 16 GT 16 PoE USB
 T(P)GS-L5208MGT 8 10/100/1000T (PoE at) + 2 1G/2.5G Copper EN50155 OS3 Managed Switch 2 2.5G 8 GT 8 PoE USB	 T(P)GS-L5208MGF 8 10/100/1000T (PoE at) + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 2 2.5G 8 GT 8 PoE USB	 T(P)ES-L5424MGFT 24 10/100TX (PoE at) + 2 1G/2.5G copper + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 4 2.5G 24 TX 24 PoE USB	 T(P)ES-L5424MGT 24 10/100TX (PoE at) + 4 1G/2.5G copper EN50155 OS3 Managed Switch 4 2.5G 24 TX 24 PoE USB
 T(P)ES-L5416MGFT 16 10/100TX (PoE at) + 2 1G/2.5G Copper + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 4 2.5G 16 TX 16 PoE USB	 T(P)ES-L5416MGT 16 10/100TX (PoE at) + 4 1G/2.5G Copper EN50155 OS3 Managed Switch 4 2.5G 16 TX 16 PoE USB	 T(P)ES-L5408MGFT 8 10/100TX (PoE at) + 2 1G/2.5G Copper + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 4 2.5G 8 TX 8 PoE USB	 T(P)ES-L5408MGT 8 10/100TX (PoE at) + 4 1G/2.5G Copper EN50155 OS3 Managed Switch 4 2.5G 8 TX 8 PoE USB
 T(P)ES-L5216MGT 16 10/100TX (PoE at) + 2 1G/2.5G copper EN50155 OS3 Managed Switch 2 2.5G 16 TX 16 PoE USB	 T(P)ES-L5216MGF 16 10/100TX (PoE at) + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 2 2.5G 16 TX 16 PoE USB	 T(P)ES-L5208MGT 8 10/100TX (PoE at) + 2 1G/2.5G copper EN50155 OS3 Managed Switch 2 2.5G 8 TX 8 PoE USB	 T(P)ES-L5208MGF 8 10/100TX (PoE at) + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 2 2.5G 8 TX 8 PoE USB

Model name (P) = PoE model

Industrial Solutions

Hardened Ethernet Connections

Ethernet Connections

Accessories

Learn more



EN50155 Rackmount Ethernet Switches

OS3 Platform

 T(P)GS-L6408XFTR 8 10/100/1000T (PoE at) + 2 10G Copper + 2 10G Q-ODC fiber EN50155 OS3 Managed Switch 4 10G 8 GT 8 PoE USB	 T(P)GS-L6408XTR 8 10/100/1000T (PoE at) + 4 10G Copper EN50155 OS3 Managed Switch 4 10G 8 GT 8 PoE USB	 T(P)GS-L5408MGFTR 8 10/100/1000T (PoE at) + 2 1G/ 2.5G Copper + 2 1G/2.5G Q-ODC fiber EN50155 OS3 Managed Switch 4 2.5G 8 GT 8 PoE USB	 T(P)GS-L5408MGTR 8 10/100/1000T (PoE at) + 2 1G/2.5G Copper EN50155 OS3 Managed Switch 4 2.5G 8 GT 8 PoE USB
--	---	--	---

EN50155 Giga Uplinks Managed Ethernet Switches

OS3 Platform

 T(P)GS-L5016T 16 10/100/1000T (PoE at) EN50155 OS3 Managed Switch 16 GT 16 PoE USB	 T(P)GS-L5012T 12 10/100/1000T (PoE at) EN50155 OS3 Managed Switch 12 GT 8 PoE USB	 T(P)ES-L5408T 8 10/100TX (PoE at) + 4 Giga Copper Uplinks EN50155 OS3 Managed Switch 4 GT 8 TX 8 PoE USB	Learn more 
--	---	---	--

OS1 Platform

 T(P)GS-5208GF 8 10/100/1000T (PoE at) + 2 1000FX L2+ EN50155 Managed Switch 2 Q-ODC 8 GT 8 PoE	 T(P)GS-5010T 10 10/100/1000T (w/ 8 PoE at) L2+ EN50155 Managed Switch 10 GT 8 PoE	 T(P)GS-5008T 8 10/100/1000T (PoE at) L2+ EN50155 Managed Switch 8 GT 8 PoE	 T(P)ES-5416T 16 10/100TX (PoE at) + 4 10/100/1000T L2+ EN50155 Managed Switch 4 GT 16 TX 16 PoE
 T(P)ES-5408T 8 10/100TX (PoE at) + 4 10/100/1000T L2+ EN50155 Managed Switch 4 GT 8 TX 8 PoE	 T(P)ES-5424DFT 24 10/100TX (PoE at) + 2 10/100/1000T + 2 100/1000FX L2+ EN50155 Managed Switch 2 GT 2 Q-ODC 24 TX 24 PoE	 T(P)ES-5424T 24 10/100TX (PoE at) + 4 10/100/1000T L2+ EN50155 Managed Switch 4 GT 24 TX 24 PoE	 I(P)GS-5008T 8 10/100/1000T (PoE at) L2+ EN50155 Managed Switch 8 GT 8 PoE
 I(P)ES-5416T 16 10/100TX (PoE at) + 4 10/100/1000T L2+ EN50155 Managed Switch 4 GT 16 TX 16 PoE	 I(P)ES-5408T 8 10/100TX (PoE at) + 4 10/100/1000T L2+ EN50155 Managed Switch 4 GT 8 TX 8 PoE	 I(P)ES-5408S 8 10/100TX (PoE at) + 4 10/100/1000T L2+ EN50155 Managed Switch 4 GT 8 TX 8 PoE	 I(P)ES-5208DF 8 10/100TX (PoE at) + 2 100/1000FX L2+ EN50155 Managed Switch 2 FX 8 TX 8 PoE

Model name (P) = PoE model

EN50155 Unmanaged Ethernet Switches



60W High Power PoE

Lantech increases the maximum PoE power available by utilizing all four pairs of the structured wiring. Lantech Ethernet PoE switches provide up to 60W per port, while also being backward compatible to 802.3at/af PoE standards. *Available in models: TPGS-0010T & TPGS-0208GF series

Ignition Sensing

Ignition sense allows you to delay power off your Ethernet switch with a designated time delay. *Available in models: 0008CA series

ITxPT Compliant

ITxPT is a Belgium-based association that supports the deployment of standards for onboard plug-and-play IT-systems applied to public transport. ITxPT compliant devices are tested in real operational conditions. This supports the adoption of plug-and-play systems by limiting the risks associated with the integration stage.

*Available models: 0008CA series

Product Line-ups

 TPGS-0010T 10 10/100/1000T (8 PoE at) EN50155 Unmanaged Switch 10 GT 8 PoE	 TPGS-0208GF 8 10/100/1000T (PoE at) + 2 1000FX EN50155 Unmanaged Switch 2 1000FX 8 GT 8 PoE	 TPGS-0008CA 8 10/100/1000T (PoE at) EN50155 Unmanaged Switch 8 GT 8 PoE	 TPES-0008CA 8 10/100TX (PoE at) EN50155 Unmanaged Switch 8 TX 8 PoE
 IPES-0208GF 8 10/100TX (PoE at) + 2 1000FX EN50155 Unmanaged Switch 2 1000FX 8 TX 8 PoE	 IPES-0208T 8 10/100TX (PoE at) + 2 10/100/1000T EN50155 Unmanaged Switch 2 GT 8 TX 8 PoE	 IPES-0008A 8 10/100TX (PoE at) EN50155 Unmanaged Switch 8 TX 8 PoE	 IPES-0008B 8 10/100TX (PoE at) EN50155 Unmanaged Switch 8 TX 8 PoE
 IPES-0005B 5 10/100TX (PoE at) EN50155 Unmanaged Switch 5 TX 5 PoE	 IPES-0101T 1 10/100TX (PoE at) + 1 10/100TX EN50155 Unmanaged Switch 2 TX 1 PoE		Learn more 

Model name (P) = PoE model

Industrial L3/10G (PoE) Ethernet Switches

10G Uplink & L3 Capacity

Lantech OS3 IP30 switch series have 10G uplinks and upgradable L3 capacity that is able to boost the outdoor network to higher bandwidth across different subnets.

Flexible Modularity & L3 Upgradable**

Lantech provides highly customized modular models to satisfy all kinds of needs, from 100TX to dual speed SFP. All 6000 series models are able to upgrade to Layer 3 (**optional).

USB Port for Backup and Configuration

With the special-designed USB port, backup / restore configuration is easier than ever! Simply plug in the USB thumb drive and the system will automatically detect and decide the action. No laptop or console needed.

Configurable Power Budget (PoE model)

To prevent over consumption that causes the system to become unstable, Lantech PoE switches are able to control the power budget by limiting the total power consumption for all connected PDs. Each port's power limit can be defined as well.

Feed 30W Power – 802.3at (PoE model)

IEEE802.3at standard is able to feed up to 30W at each PoE port, which is twice as the previous 802.3af standard. It's ideal for big power consumption devices such as PTZ IP cameras, High power wireless AP, etc.

Built-in Power Converter

Normally in vehicle environments, 48V power supply is not available. The built-in power converter is able to boost up from 12V (car), 24V (bus), and step down 110V, making the devices function well.

PoE Detection and Scheduling (PoE model)

PoE detection can detect if the connected PD hangs and then restart the PD; PoE scheduling allows pre-set power feeding schedule upon a routine time table. Each PoE port can be enabled/disabled, get the voltage, current, Watt, and temperature info displayed on WebUI. It saves both time and energy. Built-in power converter is able to boost up from 12V/24V, and step down from 110V (vary on models).

Product Line-ups OS3 Platform



I(P)GS-6300-2P

4 Modular-Slots
w/4/2 x1G/2.5G/10G SFP+
+ 2 10GT uplink

Industrial Managed Ethernet Switch



I(P)GS-L6424XSFP

24 10/100/1000T (PoE at/af)
+ 4 1G/2.5G/10G SFP

Industrial Managed Ethernet Switch



I(P)GS-6416XSFP

16 10/100/1000T (PoE at/af)
+ 4 1G/2.5G/10G SFP+

Industrial Managed Ethernet Switch



I(P)GS-6488XSFP

8 10/100/1000T (PoE) + 8 100M/1G
SFP + 4 1G/2.5G/10G SFP+

Industrial Managed Ethernet Switch



Do you know?

Lantech switch can inject IP message to 3rd party CMS like Milestone for specific applications.



Do you know?

"P" in model name means PoE capacity.



Do you know?

OS3 series is able to upgrade to Layer 3 or L3L. (optional)

Model name (P) = PoE model

Industrial Managed (PoE) Ethernet Switches

Product Line-ups

OS3 Platform  I(P)GS-L5424MGSFP 24 10/100/1000T (PoE at/af) + 4 1G/2.5G SFP Industrial Managed Ethernet Switch 	OS1 Platform  I(P)GS-5400-2P 4 Modular-Slots L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)GS-5424 24 10/100/1000T (PoE at/af) + 4 Dual Speed SFP L2+ Industrial Managed Ethernet Switch 	
OS1 Platform  IGS-5816-2P 8 10/100/1000T + 16 Dual Speed SFP L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)ES-3424DSFP-2P 24 10/100TX (PoE at/af) + 4 Dual Speed SFP L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)GS-5416MGSFP 16 10/100/1000T (PoE at/af) + 4 1G/2.5G SFP L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)GS-5488MGSFP 8 10/100/1000T (PoE) + 8 100M/1G SFP + 4 1G/2.5G SFP L2+ Industrial Managed Ethernet Switch 
OS1 Platform  I(P)GS-5408DFT 8 10/100/1000T (PoE) + 2 Dual Speed SFP + 2 10/100/1000T L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)GS-5408GSFP 8 10/100/1000T (PoE) + 4 1000M SFP L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)GS-3408GSFP 8 10/100/1000T (PoE) + 4 1000M SFP L2+ Industrial Managed Ethernet Switch 	OS2 Platform  I(P)GS-3208GSFP 8 10/100/1000T (PoE) + 2 1000M SFP L2+ Industrial Managed Ethernet Switch 
OS2 Platform  I(P)GS-3208C 8 10/100/1000T (PoE) + 2 10/100/1000T/Dual Speed SFP Combo L2+ Industrial Managed Ethernet Switch 	OS2 Platform  I(P)GS-3204MGSFP 4 10/100/1000T (PoE) + 2 1G/2.5G SFP L2+ Industrial Managed Ethernet Switch 	OS2 Platform  I(P)GS-3008 8 10/100/1000T (PoE) L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)ES-3416DSFP 16 10/100TX (PoE) + 4 Dual Speed SFP L2+ Industrial Managed Ethernet Switch 
OS1 Platform  I(P)ES-5408DFT 8 10/100TX (PoE) + 2 10/100/1000T + 2 Dual Speed SFP L2+ Industrial Managed Ethernet Switch 	OS1 Platform  I(P)ES-3408GSFP 8 10/100TX (PoE) + 4 1000M SFP L2+ Industrial Managed Ethernet Switch 	2000 Series  I(P)ES-2208CB 8 10/100TX (PoE) + 4 10/100/1000T/Dual Speed SFP Combo L2+ Industrial Managed Ethernet Switch 	2000 Series  I(P)ES-2204F 4 10/100TX (PoE) + 2 100M SFP L2+ Industrial Managed Ethernet Switch 

Model name (P) = PoE model

Industrial Unmanaged (PoE) Ethernet

Built-in Power Converter

Normally in rolling stock and vehicle environments, 48V power supply is not available. The built-in power converter is able to boost up from 12V (car), 24V (bus), and step down 110V (train), making the devices function well.

Feed 30W Power – 802.3at (PoE model)

IEEE802.3at standard is able to feed up to 30W to each PoE port, which is twice as the previous 802.3af standard. It's ideal for big power consumption devices such as PTZ IP cameras, High power wireless AP, etc.

E-Marking Certified

The E-marking certificate makes it the most suitable PoE switch for bus, carriage, other vehicles application as well as for industrial areas where the power source is limited with 12V but has demand of IP surveillance or VoIP applications. (12V model)



Product Line-ups

 I(P)GS-0208GSFP 8 10/100/1000T (PoE at/af) + 2 1000M SFP Industrial Ethernet Switch 2 SFP 8 GT 8 PoE	 I(P)GS-0208C 8 10/100/1000T (PoE at/af) + 2 10/100/1000T/Dual Speed SFP Combo Industrial Ethernet Switch 2 Combo 8 GT 8 PoE	 I(P)GS-0008B 8 10/100/1000T (PoE at/af) Industrial Ethernet Switch 8 GT 8 PoE	 I(P)GS-0204DSFP 4 10/100/1000T (PoE) + 2 Dual Speed SFP Industrial Ethernet Switch 2 SFP 4 GT 4 PoE
 IPGS-0005T-4 5 10/100/1000T w/ 4 PoE at/af Industrial Ethernet Switch 5 GT 4 PoE	 IPGS-0101T Industrial Gigabit Switch with PoE 802.3at/af 2 GT 1 PoE	 I(P)ES-0208CA 8 10/100TX (PoE at/af) + 2 10/100/1000T/Dual Speed SFP Combo Industrial Ethernet Switch 2 Combo 8 TX 8 PoE	 IPES-0104GT-4 4 10/100TX PoE at/af + 1 10/100/1000T Industrial Ethernet Switch 1 GT 4 TX 4 PoE
 I(P)ES-0204DFT-4 4 10/100TX (PoE at/af) + 1 10/100/1000T + 1 Dual Speed SFP Industrial Ethernet Switch 2 SFP 4 TX 4 PoE	 I(P)ES-0008B 8 10/100TX (PoE) Industrial Ethernet Switch 8 TX 8 PoE	 I(P)GC-0101DSFP 10/100/1000T to 100/1000M SFP 802.3at Industrial PoE Switch Converter 1 SFP 1 GT 1 PoE	

Model name (P) = PoE model

Industrial IEC 61850-3 Ethernet Switches



IEC 61850-3 / IEEE 1613 Certified

The series complies with the strict substation-rated standard of IEC 61850-3 and IEEE 1613. It is able to help against electrical interference and meets communication requirements for network equipment used in power substations. For example, the switch was tested with high ESD of up to 8K (contact) and 15K (air).

Zero GOOSE Message Packet Loss

The series supports standardized GOOSE messages that ensure the most critical packets are transmitted. The manager is able to receive and react in unexpected accidents in real time without any packet loss.

IEC61850-90-4 switch data modeling

Lantech IEC 61850-3 model embeds a MMS server based on IEC61850-90-4 switch data modeling for power SCADA that allow power SCADA to control and monitor the switch without additional NMS.

Product Line-ups OS1 Platform



I(P)GS-5400-2P-PT
4 Modular Slots Industrial L2+ IEC 61850-3 Managed (PoE) Switch

Max 24GT Max 18FX Max 32SFP Max 24PoE USB



I(P)GS-5424-PT
24 10/100/1000T (PoE) + 4 DualSpeed SFP IEC 61850-3 Managed Ethernet Switch

24 GT 4 SFP 24 PoE USB



I(P)ES-3424DSFP-2P-PT
24 10/100TX (PoE) + 4 DualSpeed SFP IEC 61850-3 Managed Ethernet Switch

4 SFP 24 TX 24 PoE USB



I(P)GS-5408DFT-PT
2 10/100/1000T + 2 100/1000 SFP + 8 10/100/1000T (PoE) IEC 61850-3 Industrial Managed Ethernet Switch

10 GT 2 SFP 8 PoE USB



I(P)ES-5408DFT-PT
8 10/100TX (PoE) + 2 10/100/1000T + 2 Dual Speed SFP L2+ Industrial Managed Ethernet Switch

2 GT 4 SFP 8 TX



Do you know?

The series built-in MMS:

- IP address information
- Environmental Monitoring
- PoE status
- Port status
- Packet statistics

Model name (P) = PoE model

Industrial DNV Type Ethernet Switches

DNV Certified

DNV (Det Norske Veritas) is a certification that verifies maritime facilities comply for satisfactory operation in typical on-board environments. All the certified switches are designed to create a reliable solution for marine applications.

Strict EMC Tests

To meet the robustness that maritime applications required, Lantech DNV-certified switches passed several immunity tests, including conducted low frequency test, electrical transient/burst test, conducted radio frequency test, etc.

Prevent Compass Interference

In order to not interfere with a standard or with the steering magnetic compass installed for maritime applications, Lantech DNV-certified switches are tested for compass safe distance in accordance with IEC 60945.

Anti-Vibration

Three perpendicular plans (different frequency/amplitude) are adopted to ensure the switches are able to function normally during and after intensive vibration in maritime environments.



Product Line-ups

LGS-2624C-DNV

20 10/100/1000T + 4 1000T/
100/1000M SFP Combo + 2 100/
1000M SFP L2+ Managed Switch



IES-2208CA-DNV

8 10/100TX + 2 10/100/1000T/
Dual Speed SFP Combo
Industrial Managed Ethernet Switch



IES-2008B-DNV

8 10/100TX
Industrial Managed Ethernet Switch



Do you know?

DNV GL is a globally leading quality assurance and risk management company founded in 1864 in Oslo, Norway.

Industrial Hazardous Ethernet Switches



UL Class 1 Division 2 Certified

Established by well-known Underwriters Laboratories (UL), "UL Class I Division II" is one of the most widely used safety certifications. All models are strictly tested by UL Class I Division II standard for group A, B, C, D, which covers most hazardous atmospheres.

ATEX Certified

The ATEX Directive 94/9/EC is a directive adopted by the European Union (EU) to facilitate free trade in the EU by aligning the technical and legal requirements in the Member States for products intended for use in potentially explosive atmospheres.

Non-sparking Components

To meet the standard of UL Class I Division II and ATEX, Lantech designs our hazardous series with an apparatus that normally has no arcing parts or thermal effects capable of ignition. Also, the components are hermetically sealed.

Non-incendive Design

Lantech hazardous series is incapable of igniting specified flammable gas-air or vapor-air mixture. The housing of a non-incendive component is not intended to exclude the flammable atmosphere or contain an explosion.

Product Line-ups



IES-2208CA (-ATEX)
8 10/100TX + 2 10/100/1000T/
Dual Speed SFP Combo
Industrial Managed Switch



IES-2008B (-ATEX)
8 10/100TX
Industrial Managed Ethernet Switch



IES-0008T
8 10/100TX
Industrial Unmanaged Switch



Do you know?

Lantech certified models provide up to Gigabit rapid speed and reliable Pro-Ring redundant protection.

Industrial Entry Ethernet Switches

 IGS-0016 16 10/100/1000T Industrial Unmanaged Switch 16 GT	 IGS-0208GSFP 8 10/100/1000T + 2 1000M SFP Industrial Unmanaged Switch 2 SFP 8 GT	 IGS-0204DSFP 4 10/100/1000T + 2 Dual Speed SFP Industrial Unmanaged Switch 2 SFP 4 GT	 IGS-0008B 8 10/100/1000T Industrial Unmanaged Switch 8 GT
 IES-0208CA 8 10/100TX + 2 10/100/1000T/ Dual Speed SFP Combo Industrial Unmanaged Switch 2 Combo 8 TX	 IES-0204DFT 4 10/100TX + 1 10/100/1000T + 1 Dual Speed SFP Industrial Unmanaged Switch 1 SFP 1 GT 4 TX	 IES-0204FT 4 10/100TX + 2 100FX Industrial Unmanaged Switch 2 FX 4 TX	 IES-0104FT 4 10/100TX + 1 100FX Industrial Unmanaged Switch 1 FX 4 TX
 IES-0016 16 10/100TX Industrial Unmanaged Switch 16 TX	 IES-0008B 8 10/100TX Industrial Unmanaged Switch 8 TX	 IES-0008T 8 10/100TX Industrial Unmanaged Switch 8 TX	 IES-0005T 5 10/100TX Industrial Unmanaged Switch 5 TX

Industrial Converter Series

 IPGC-0101DSFP 10/100/1000T to 100/1000M SFP SFP 802.3at Industrial PoE Switch Converter 1 SFP 1 GT 1 PoE	 IGC-0101DSFP 10/100/1000T to 100/1000M SFP Industrial Switch Converter 1 SFP 1 GT	 IGS-022DSFP 1 100M/1000M SFP + 1 1000M SFP Industrial Ethernet Switch Converter 2 SFP	
---	--	---	--



Serial Devices



LSC-1102B
Ethernet to RS-232/ 422/ 485
Serial Device



LSC-0101U
USB to RS-422/485 Serial Device




Central Managed Ethernet Switches



LPGS-2424C-240W
24 10/100/1000T + 4 1000T/
100/1000M SFP Combo L2 PoE af/at
Gigabit Managed Ethernet Switch



LGS-2624C
20 10/100/1000T + 4 1000T/100/
1000M SFP Combo + 2 100/1000M
SFP L2+ Managed Switch



PoE Series



POA-1000A
Single Port PoE Power Source
Injector IEEE802.3at/af PoE,
10/100/1000Mbps LAN



POA-100B
Single Port PoE Power Source
Injector IEEE802.3at/af PoE,
10/100Mbps LAN



POS-100A
Adjustable Output
Power Over Ethernet Splitter



Fiber Converters

 CM-121 10/100/1000BaseT to 1000M SFP Web Smart Fiber Media Converter 1 GT 1 SFP	 CM-022A 100/1000Base SFP to 100/1000Base SFP Media Converter 1 SFP 1 SFP	 CM-021DSFP Gigabit Ethernet 10/100/1000Base-T to 100/1000Base-X Media Converter 1 GT 1 SFP	 CM-011A 10/100TX to 100FX Media Converter 1 TX 1 SFP
 MC-116-RPS 16 slots Universal Media Converter Chassis Supported Models: CM-121 CM-022A CM-011A			

Products Naming Rule

TPES-R6416TA-8-PT-MM-XL-XAC-2S-67-12V-BB

T: Hardened (Industrial grade)
P: PoE
E: Major ports are 10/100TX Ethernet
S: Switch
R: Router
A: Access Point
P: PoE

6: 10G uplinks
4: L2+ managed
1: L2 managed
6: L2 managed
1: Smart managed
6: Unmanaged

16: # of uplink ports

T: OS4
A: OS3

8: # of major ports

PT: IEC 61850-3 compliance

MM: Multi mode fiber
XL: Multi mode fiber

XAC: Q-ODC connector
2S: 2 serial ports

67: IP67 housing
12V: Input power:
12V=9.5~56VDC
72V=50.4~90VDC
110V=43~137.5VDC
HV=90~305VAC/120~430VDC
WV=16.8~137.5VDC
WV=WV with isolation
LDC=36~85VDC
AC=85~265VAC IEC320
2P=Dual embedded power

BB: 2-pairs bypass
B: 1-pair bypass
BT: 1-pair copper bypass
BBT: 2-pairs copper bypass
BF: 1-pair fiber bypass
BBF: 2-pairs fiber bypass

C: Combo
F: Fiber
DF: Dual speed fiber
GF: Giga fiber
T/GT: Giga T
GSFP: 1000M SFP
DSFP: Dual speed SFP
DFT: Dual speed fiber + Giga T
AC: 802.11AC wireless
S: Compact size
XSFP(IP30): 1G/2.5G/10G SFP
MGSFP(IP30): 1G/2.5G SFP
XT: 1G/2.5G/5G/10G Copper
XF: 1G/2.5G/5G/10G Fiber
XFT: XT+XF
MGT: 1G/2.5G Copper
MGF: 1G/2.5G Fiber
MGFT: MGT+MGF

2L: 2 LTE modules
1L: 1 LTE module
2AC: 2 802.11AC modules
1AC: 1 802.11AC module
WW: Worldwide LTE band
EUNA: Europe / North America LTE band
APAC: Asia Pacific LTE band

Accessories



ANT11000090



ANT11000091



ANT11000092



**ANT11000041
ANT11000042
ANT11000051**



**ANT11000044
ANT11000045
ANT11000055**

Multifunction Antenna

Part Number	Antenna Type	Band	Casing	Dimension	Gain
ANT11000091	5-in-1 2G/3G/4G MIMO (x2) GPS/GLONASS/GALILEO (x1) MIMO Dualband 802.11ac (x2)	2G/3G/4G MIMO : 698~960MHz, 1710~2170MHz, 2300~2700 MHz GPS/GLONASS/GALILEO (1575.42/1602MHz) Wi-Fi 2.4GHz / 5GHz (MIMO) x2	IP67, Screw Mount	Height 85.7mm x Diameter 145.6mm	3dBi
ANT11000092	6-in-1 2G/3G/4G MIMO (x2) GPS/GLONASS/GALILEO/BeiDou (x1) Wi-Fi 2.4G/5GHz (x1) AM/FM (x1) DSRC 5.9GHz (x1)	2G/3G/4G MIMO : 698~960MHz, 1710~2170MHz, 2300~2700 MHz GPS/GLONASS/GALILEO/Bei Dou (1561/1575.42/1602MHz)	IP67, Screw Mount	176.2 x 84.5 x 70.8mm (LxWxH)	6dBi

Cellular Antenna

Part Number	Antenna Type	Band	Casing	Dimension	Gain
ANT11000041	2G/3G/4G dipole antenna EU type	791-960/ 1710~2170/ 2500~2700MHz	Plastic	162.2 x 19.6 x 13.5mm (LxWxH)	3dBi
ANT11000042	2G/3G/4G dipole antenna US type	704-960/1710~2170MHz	Plastic	162.2 x 19.6 x 13.5mm (LxWxH)	3dBi
ANT11000044	2G/3G/4G dipole antenna EU type	704-960/1710~2690MHz	Plastic	105 x 27 x 9.4mm (LxWxH)	1.6dBi
ANT11000045	2G/3G/4G dipole antenna US type	698-960/1710~2690MHz	Plastic	105 x 27 x 9.4mm (LxWxH)	3dBi

Wi-Fi Antenna

Part Number	Antenna Type	Band	Casing	Dimension	Gain
ANT11000051	SMA dipole antenna	2.4/5GHz	Plastic	162.2 x 19.6 x 13.5mm (LxWxH)	3dBi (2.4GHz) 4dBi (5GHz)
ANT11000055	SMA dipole antenna	2.4/5GHz	Plastic	105 x 27 x 9.4mm (LxWxH)	6dBi (2.4GHz) 4dBi (5GHz)
ANT11000090	802.11ac 3x3 MIMO	2.4/5GHz	IP67, Screw Mount	Height 65.35mm x Diameter 147.5mm	5dBi

Antenna Base

Part Number	Description
ADA11000052	Magnetic antenna base for Wi-Fi, RP SMA Jack Base, Length : 1M
ADA11000053	Magnetic antenna base for 3G/4G, RP SMA Jack Base, Length : 1M



ADA11000052 / AD11000053

SFP (Mini-GBIC)

DDM SFP All SFP part no. with D have Diagnostic function

SFP 10Gbps

Part Number	Wavelength	LD	IO	LOS	Mode	Link	Temp.
8330-193D	850nm	VCSEL	AC/AC	TTL	Multi-mode	300m	-10~70°C
8330-194D	1310nm	DFB	AC/AC	TTL	Single-mode	10km	-10~70°C
8330-200D	1270nm	DFB	AC/AC	TTL	Single-mode	20km	-10~70°C
8330-201D	1330nm	DFB	AC/AC	TTL	Single-mode	20km	-10~70°C
8330-202D	1270nm	DFB	AC/AC	TTL	Single-mode	40km	-10~70°C
8330-203D	1330nm	DFB	AC/AC	TTL	Single-mode	40km	-10~70°C
8330-193D-E	850nm	VCSEL	AC/AC	TTL	Multi-mode	300m	-40~85°C
8330-194D-E	1310nm	DFB	AC/AC	TTL	Single-mode	10km	-40~85°C
8330-200D-E	1270nm	DFB	AC/AC	TTL	Single-mode	20km	-40~85°C
8330-201D-E	1330nm	DFB	AC/AC	TTL	Single-mode	20km	-40~85°C
8330-202D-E	1270nm	DFB	AC/AC	TTL	Single-mode	40km	-40~85°C
8330-203D-E	1330nm	DFB	AC/AC	TTL	Single-mode	40km	-40~85°C

SFP 2.5Gbps

Part Number	Wavelength	LD	IO	LOS	Mode	Link	Temp.
8330-262D	850 nm	VCSEL	AC/AC	TTL	Multi-mode	300m	-10~70°C
8330-263D	1310 nm	FP	AC/AC	TTL	Single-mode	2km	-10~70°C
8330-265D	1310 nm	DFB	AC/AC	TTL	Single-mode	15km	-10~70°C
8330-262D-E	850 nm	VCSEL	AC/AC	TTL	Multi-mode	300m	-40~85°C
8330-263D-E	1310 nm	FP	AC/AC	TTL	Single-mode	2km	-40~85°C
8330-265D-E	1310 nm	DFB	AC/AC	TTL	Single-mode	15km	-40~85°C

SFP 1.25Gbps

Part Number	Wavelength	LD	IO	LOS	Mode	Link	Temp.
8330-162	850 nm	VCSEL	AC/AC	TTL	Multi-mode	550m	-10~70°C
8330-163	1310 nm	FP	AC/AC	TTL	Multi-mode	2km	-10~70°C
8330-165	1310 nm	FP	AC/AC	TTL	Single-mode	10km	-10~70°C
8340-0591	1310 nm	DFB	AC/AC	TTL	Single-mode	40km	-10~70°C
8330-166	1550 nm	DFB	AC/AC	TTL	Single-mode	50km	-10~70°C
8330-169	1550 nm	DFB	AC/AC	TTL	Single-mode	60km	-10~70°C
8330-170	1550 nm	DFB	AC/AC	TTL	Single-mode	80km	-10~70°C
8330-167	1550 nm	DFB	AC/AC	TTL	Single-mode	120km	-10~70°C
8330-162-E	850 nm	VCSEL	AC/AC	TTL	Multi-mode	550m	-40~85°C
8330-163-E	1310 nm	FP	AC/AC	TTL	Multi-mode	2km	-40~85°C
8330-165-E	1310 nm	FP	AC/AC	TTL	Single-mode	10km	-40~85°C
8340-0591-E	1310 nm	DFB	AC/AC	TTL	Single-mode	40km	-40~85°C
8330-166-E	1550 nm	DFB	AC/AC	TTL	Single-mode	50km	-40~85°C
8330-169-E	1550 nm	DFB	AC/AC	TTL	Single-mode	60km	-40~85°C
8330-167-E	1550 nm	DFB	AC/AC	TTL	Single-mode	80km	-40~85°C
8330-170-E	1550 nm	DFB	AC/AC	TTL	Single-mode	120km	-40~85°C

SFP 125Mbps

Part Number	Wavelength	LD	IO	LOS	Mode	Link	Temp.
8330-060	1310nm	FP	AC/AC	TTL	Multi-mode	2km	-10~70°C
8330-065	1310nm	FP	AC/AC	TTL	Multi-mode	5km	-10~70°C
8330-061	1310nm	FP	AC/AC	TTL	Single-mode	30km	-10~70°C
8330-060-E	1310nm	FP	AC/AC	TTL	Multi-mode	2km	-40~85°C
8330-065-E	1310nm	FP	AC/AC	TTL	Multi-mode	5km	-40~85°C
8330-061-E	1310nm	FP	AC/AC	TTL	Single-mode	30km	-40~85°C

SFP 1000T

Part Number	Description
8330-168	10/100/1000Base-T, SFP, 100m, 3.3V, -10~70°C
8330-168-E	10/100/1000Base-T, SFP, 100m, 3.3V, -40~85°C

125Mbps/1.25Gbps Dual-rate

Part Number	Wavelength	LD	IO	LOS	Mode	Link	Temp.
8330-191	1310nm	FP	AC/AC	TTL	Single-mode	10km	-10~70°C
8330-191-E	1310nm	FP	AC/AC	TTL	Single-mode	10km	-40~85°C

BIDI SFP 1.25Gbps

Part Number	TX	LD	RX	IO	LOS	Link	Temp.
8330-197	1310nm	FP	1550nm	AC/AC	TTL	0.5km	-10~70°C
8330-195	1310nm	FP	1550nm	AC/AC	TTL	2km	-10~70°C
8330-188	1310nm	FP	1550nm	AC/AC	TTL	10km	-10~70°C
8330-186	1310nm	FP	1550nm	AC/AC	TTL	20km	-10~70°C
8330-180	1310nm	DFB	1550nm	AC/AC	TTL	40km	-10~70°C
8330-181	1310nm	DFB	1550nm	AC/AC	TTL	60km	-10~70°C
8330-184	1490nm	DFB	1550nm	AC/AC	TTL	80km	-10~70°C
8330-197-E	1310nm	FP	1550nm	AC/AC	TTL	0.5km	-40~85°C
8330-195-E	1310nm	FP	1550nm	AC/AC	TTL	2km	-40~85°C
8330-188-E	1310nm	FP	1550nm	AC/AC	TTL	10km	-40~85°C
8330-186-E	1310nm	FP	1550nm	AC/AC	TTL	20km	-40~85°C
8330-180-E	1310nm	DFB	1550nm	AC/AC	TTL	40km	-40~85°C
8330-181-E	1310nm	DFB	1550nm	AC/AC	TTL	60km	-40~85°C
8330-184-E	1490nm	DFB	1550nm	AC/AC	TTL	80km	-40~85°C
8330-198	1550nm	FP	1310nm	AC/AC	TTL	0.5km	-10~70°C
8330-196	1550nm	FP	1310nm	AC/AC	TTL	2km	-10~70°C
8330-189	1550nm	DFB	1310nm	AC/AC	TTL	10km	-10~70°C
8330-187-E	1550nm	DFB	1310nm	AC/AC	TTL	20km	-10~70°C
8330-182-E	1550nm	DFB	1310nm	AC/AC	TTL	40km	-10~70°C
8330-183-E	1550nm	DFB	1310nm	AC/AC	TTL	60km	-10~70°C
8330-185-E	1550nm	DFB	1490nm	AC/AC	TTL	80km	-10~70°C

BIDI SFP 125Mbps

Part Number	TX	LD	RX	IO	LOS	Link	Temp.
8330-071	1310nm	FP	1550nm	AC/AC	TTL	2km	-10~70°C
8330-069	1310nm	FP	1550nm	AC/AC	TTL	20km	-10~70°C
8330-080	1310nm	FP	1550nm	AC/AC	TTL	40km	-10~70°C
8330-081	1310nm	FP	1550nm	AC/AC	TTL	60km	-10~70°C
8330-084	1310nm	FP	1550nm	AC/AC	TTL	80km	-10~70°C
8330-071-E	1310nm	FP	1550nm	AC/AC	TTL	2km	-40~85°C
8330-069-E	1310nm	FP	1550nm	AC/AC	TTL	20km	-40~85°C
8330-080-E	1310nm	FP	1550nm	AC/AC	TTL	40km	-40~85°C
8330-081-E	1310nm	FP	1550nm	AC/AC	TTL	60km	-40~85°C
8330-084-E	1310nm	FP	1550nm	AC/AC	TTL	80km	-40~85°C
8330-072	1550nm	FP	1310nm	AC/AC	TTL	2km	-10~70°C
8330-068	1550nm	FP	1310nm	AC/AC	TTL	20km	-10~70°C
8330-082	1550nm	DFB	1310nm	AC/AC	TTL	40km	-10~70°C
8330-083	1550nm	DFB	1310nm	AC/AC	TTL	60km	-10~70°C
8330-085	1550nm	DFB	1310nm	AC/AC	TTL	80km	-10~70°C
8330-072-E	1550nm	FP	1310nm	AC/AC	TTL	2km	-40~85°C
8330-068-E	1550nm	FP	1310nm	AC/AC	TTL	20km	-40~85°C
8330-082-E	1550nm	DFB	1310nm	AC/AC	TTL	40km	-40~85°C
8330-083-E	1550nm	DFB	1310nm	AC/AC	TTL	60km	-40~85°C
8330-085-E	1550nm	DFB	1310nm	AC/AC	TTL	80km	-40~85°C



Bracket



Part Number	Description
MBAK19002	L-Bracket that can change 90 degree of DIN rail mounting
MBAK19003	Wall mount bracket for 74 (W) x 105 (D) x 152 (H) mm / 74 (W) x 135 (D) x 152 (H) / 96 (W) x 105 (D) x 152 (H) mm Industrial Switches
MBAK19008	Wall mount bracket for 35 (W) x 105 (D) x 152 (H) mm / 43 (W) x 105 (D) x 152 (H) mm Industrial Switches
MBAK19004	19" Rack Mounting Kit for 74 (W) x 105 (D) x 152 (H) mm / 74 (W) x 135 (D) x 152 (H) mm Industrial Switches
MBAK19005	19" Rack Mounting Kit for 35 (W) x 105 (D) x 152 (H) mm Industrial Switches
MBAK19009	19" Rack Mounting Kit for 43 (W) x 105 (D) x 152 (H) mm Industrial Switches
MBAK19006	Side DIN Rail mounted fin for 74 (W) x 105 (D) x 152 (H) mm Industrial Switches
MBAK19007	Side DIN Rail mounted fin for 74 (W) x 135 (D) x 152 (H) mm Industrial Switches

Power Supply



Model	O/P voltage Adjustment	Loading (A)			Ripple Noise	Line Reg.	Load Reg.	Efficiency	Overvoltage Protection
		Min.	Rated	Max.					
MDR-20-5	4.75~5.5VDC	0A	3A	3A	80mVp-p	±1%	±1%	76.0%	5.75~6.75VDC
MDR-20-12	10.8~13.2VDC	0A	1.67A	1.67A	120mVp-p	±1%	±1%	80.0%	13.8~16.2VDC
MDR-20-24	13.5~16.5VDC	0A	1.34A	1.34A	120mVp-p	±1%	±1%	81.0%	17.25~20.25VDC
MDR-20-48	21.6~26.4VDC	0A	1A	1A	150mVp-p	±1%	±1%	84.0%	27.6~32.4VDC
MDR-40-5	5~6VDC	0A	6A	6A	80mVp-p	±1%	±1%	78.0%	6.25~7.25VDC
MDR-40-12	12~15VDC	0A	3.33A	3.33A	120mVp-p	±1%	±1%	86.0%	15.6~18VDC
MDR-40-24	24~30VDC	0A	1.7A	1.7A	150mVp-p	±1%	±1%	88.0%	31.2~36VDC
MDR-40-48	48~56VDC	0A	0.83A	0.83A	200mVp-p	±1%	±1%	88.0%	57.6~64.8VDC
MDR-75-12	12~14VDC	0A	6.3A	6.3A	80mVp-p	±0.5%	±1%	85.5%	14~17VDC
NDR-75-24	24~28VDC	0A	3.2A	3.2A	120mVp-p	±0.5%	±1%	88.0%	29~33VDC
NDR-75-48	48~55VDC	0A	1.6A	1.6A	150mVp-p	±0.5%	±1%	89.0%	56~65VDC
NDR-120-12	12~14VDC	0A	10A	10A	100mVp-p	±0.5%	±1%	85.5%	14~17VDC
NDR-120-24	24~28VDC	0A	5A	5A	120mVp-p	±0.5%	±1%	88.0%	29~33VDC
NDR-120-48	48~55VDC	0A	2.5A	2.5A	150mVp-p	±0.5%	±1%	89.0%	56~65VDC
NDR-240-24	24~28VDC	0A	10A	10A	150mVp-p	±0.5%	±1%	88.5%	29~33VDC
NDR-240-48	48~55VDC	0A	5A	5A	150mVp-p	±0.5%	±1%	90.0%	56~65VDC
NDR-480-24	24~28VDC	0A	20A	20A	150mVp-p	±0.5%	±1%	92.5%	29~33VDC
NDR-480-48	48~55VDC	0A	10A	10A	150mVp-p	±0.5%	±1%	92.5%	56~65VDC
AD1024-24F	+24VDC ±10%	0A	1A	1A	150mVp-p	±1%	±1%	83.0%	40VDC Max
AD1024-24F-E	+24VDC ±10%	0A	1A	1A	150mVp-p	±1%	±1%	83.0%	40VDC Max
AD1048-24F	+24VDC ±10%	0A	2A	2A	150mVp-p	±1%	±1%	83.0%	27~30VDC
AD1048-24F-E	+24VDC ±10%	0A	2A	2A	150mVp-p	±1%	±1%	83.0%	27~30VDC
AD1048-24FS	+24VDC ±10%	0A	2A	2A	150mVp-p	±1%	±1%	83.0%	40VDC Max
AD1048-24FS-E	+24VDC ±10%	0A	2A	2A	150mVp-p	±1%	±1%	83.0%	40VDC Max
AD1048-48F	+48VDC ±10%	0A	1A	1A	250mVp-p	±1%	±1%	83.0%	52~57VDC
AD1048-48FS	+48VDC ±10%	0A	1A	1A	250mVp-p	±1%	±1%	83.0%	60VDC Max
AD1072-24F	+24VDC ±10%	0A	3A	3A	150mVp-p	±1%	±1%	81.0%	27~30VDC
AD1072-48F	+48VDC ±10%	0A	1.5A	1.5A	250mVp-p	±1%	±1%	82.0%	52~56VDC
AD1120-24F	+24VDC ±10%	0A	5A	5A	150mVp-p	±1%	±1%	81.0%	27~30VDC
AD1120-48F	+48VDC ±10%	0A	2.5A	2.5A	550mVp-p	±1%	±1%	83.0%	52~56VDC
AD1240-24S	+24VDC ±10%	0A	10A	10A	150mVp-p	±1%	±1%	83.0%	27~30VDC
AD1240-48S	+48VDC ±10%	0A	5A	5A	250mVp-p	±1%	±1%	84.0%	52~56VDC
AD1360-24S	+24VDC ±10%	0A	15A	15A	150mVp-p	±1%	±2%	82.0%	40VDC Max
AD1360-48S	+48VDC ±10%	0A	7.5A	7.5A	250mVp-p	±1%	±2%	83.0%	52~56VDC
AD1500-24S	+24VDC ±10%	0A	21A	21A	150mVp-p	±1%	±2%	84.0%	27~30VDC
AD1500-48S	+48VDC ±10%	0A	10.5A	10.5A	250mVp-p	±1%	±2%	85.0%	52~56VDC

Note: 1. Each output can supply up to maximum current, but total loading cannot exceed rated output wattage.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 110VAC input.
4. Ripple & Noise is measured by using a 0.1µF/630V metallized capacitor & a 47µF electrolytic capacitor parallel on the test point, at rated load and 110VAC input.
5. Efficiency is measured at rated load and 110VAC input.
6. Standard Operating Temperature: -20°C ~ 50°C / ambient, derating each output at 2.5% per degree from 50°C ~ 70°C
7. Wide Operating Temperature (-E model): -40°C ~ 75°C / ambient, derating each output at 2.5% per degree from 50°C ~ 75°C, which means the output is 18 Watts at 75°C
*Note: Starting time of -E model is 1.5 to 2 seconds at -40°C

Cable



Part Number	Description	Pin Number	Type	Length	Gender
ECONM12-5P(F)70CM CABLE	A-coded 90° Power Cable	5	M12	0.7M	Female
ECONM12-5P(F)1.5M CABLE	A-coded 90° Power Cable	5	M12	1.5M	Female
ECONM23-5P(F)70CM CABLE	A-coded 90° Power Cable, Made in Taiwan	5	M23	0.7M	Female
ECONM23-5P(F)70CM CABLE-C	A-coded 90° Power Cable, Made in China	5	M23	0.7M	Female
ECONM23-5P(F)1.5M CABLE	A-coded 90° Power Cable, Made in Taiwan	5	M23	1.5M	Female
ECONM12-4P(F)1.5M CABLE	A-coded 90° Power Cable	4	M12	1.5M	Female
ECONM12-08M2-CONSOLE	A-coded 180° to RS232 cable for console	8	M12	1.5M	Male
ECABM12X83MSTP	X-coded Shielded Twisted Pair (STP) Cable	8	M12	3M	Male
ECAB124030MJS	D-coded Shielded Twisted Pair (STP) Cable	4	M12	3M	Male
ECABM002-QOP2-3.0-MM-OM3	Q-ODC 2 plug/LC multimode fiber, MM-OM3	-	Q-ODC	3M	-

Connector



ECONM23-5P(F)-S-180



ECONM23-5P(F)-S-90



ECONM12-04A(F)-C-180



ECONM12-05A(F)-C-180

Part Number	Description	Pin Number	Type	Gender
ECONM23-5P(F)-S-180	A-coded 180° Screw Type Connector	5	M23	Female
ECONM23-5P(F)-S-90	A-coded 90° Screw Type Connector	5	M23	Female
ECONM12-05A(F)-C-180	A-coded 180° Crimp Type Connector	5	M12	Female
ECONM12-04A(F)-C-180	A-coded 180° Crimp Type Connector	4	M12	Female
ECONM12-08A(M)-180	A-coded 180° Crimp Type Connector	8	M12	Male
ECONM12-05A(M)-C-180	A-coded 180° Crimp Type Connector	5	M12	Male
ECONM12-08X(M)-SPEEDCON	X-coded 180° Crimp Type Connector (shielded, SPEEDCON)	8	M12	Male
ECONM12-04D(M)-C-180	D-coded 180° Crimp Type Connector	4	M12	Male

Pioneering Industrial and IP Networks

Lantech Worldwide Offices



Taiwan

Lantech Communications Global, Inc.

7F, No.33, Sec.1, Tiding Blvd.,
Neihu District, Taipei, Taiwan, 11494
Tel: +886-2-2790-2589
Fax: +886-2-2790-2516
info@lantechcom.tw
www.lantechcom.tw

Europe

Lantech Communications Europe GmbH

Philipp-Kachel-Str. 42a
63911 Klingenberg / Germany
Tel: +49-9372-50959-97
Fax: +49-9372-50959-99
sales@lantechcom.eu
www.lantechcom.eu

Singapore

Lantech Singapore

25 Bukit Batok Crescent
#10-07 THE ELITIST
Singapore 658066
Tel: +65-8822-5589
lim@lantechcom.tw

United Kingdom

Lantech UK & Ireland Sales

The Barracks Business Centre
Wakefield Road Pontefract
West Yorkshire WF8 4HH
Mobile: +44 (0) 7746 256770
Office: +44 (0) 1977 877477
www.lantechcom.tw
ken.woolley@lantechcom.tw

USA

Lantech Communications Global, Inc.

1013 Centre Road, Suite 403S
Wilmington, DE 19805

Australia

Lantech Communications Australia

15 McCabe Street,
North Fremantle, WA 6159
Tel : +61 8 6558 0818
www.lantechcom.com.au
sales@lantechcom.com.au
Victoria Contact
Tel : +61-4-7438-1551



www.lantechcom.tw



info@lantechcom.tw

