

## TWMR-5002

**EN50155 Multifunction VPN Router w/1 WiFi 11ac + 1 LTE 4G + 2 serial ports + 2 Gigabit X-coded Ethernet for Load Balancing, VPN, Protocol Gateway, Storage\*\*; WV input; IP65/54**

- Built-in 1x WiFi 11ac/a/b/g/n module + 1xLTE 4G module + 2xGigabit X-coded ports
- Support LTE Cat 6 (APAC & EUNA models) or Cat 12/9/13 (WW model)
- Up to 2 concurrent modems for 3G/4G LTE Link & GPS(1L-1AC model/2 SIMs)
- Built-in 2 serial ports with 2.5K isolation(RS422/RS485) or w/o isolation(RS232)
- LTE 4G modem with GPS positioning & 2 SIMs fail-over
- WiFi radio for 802.11ac/a/b/g/n with 5GHz or 2.4GHz; MIMO 3T3R
- VPN router for Multi-site VPN, OpenVPN, L2TP over IPsec, IPsec, PPTP\*\*, L2 over GRE , IPGRE
- Support roaming with 802.11k & v
- Supports AP/ Bridge/Client/MESH modes
- Support 802.11s Wireless Mesh Network
- Load Balancing built-in 5 mechanism for WiFi client/WAN arrangement
- Optional EMMC Flash storage on-board\*\*
- Support NAT and Firewall
- Support Modbus or gateway on serial ports
- Galvanic isolation on WV model from 16.8V~137.5V input
- Built-in environmental monitoring for router inside info with voltage, current, temperature;
- LTE /WIFI graphic signal strength
- Editable login page of captive portal for hot-spot application
- USB port for backup, restore the configuration file and upgrade firmware; Dual image firmware\*
- IP 65 /54 Aluminum housing for best heat dissipation and preventing moist ingress
- EN50155/61373/45545 verification for railway application



### OVERVIEW

Lantech TWMR-5002 series is a next generation EN50155 multi-function VPN router w/1x 802.11ac WiFi + 1x LTE modem + 2x Gigabit Ethernet+ 2 serial ports that supports advanced function of VPN, Load-Balancing(Premium pack), EMMC Flash Storage\*\*, Protocol gateway(Modbus), Storage\*\*, WiFi roaming and LTE dual SIM fail-over for on-board / onboard-to-ground applications. The dual core CPU with 1.6GHz + 256M flash enables the router to multi-task smoothly.

#### **LTE modem 4G/3G with dual SIM fail-over**

Built-in one LTE modem with 2 SIM card slots, TWMR-5002 can allow failover between two operators for resilient connection. Both GPS and Russian GLONASS systems are supported (may vary in models)

#### **IEEE 802.11ac radio up to 1.3GMbps bandwidth**

With IEEE 802.11ac capability, TWMR-5002 can operate either 5GHz or 2.4GHz bands, offering the maximum speed of 1.3GMbps bandwidth. It is also compatible with 802.11g/n that can work with 2.4GHz for longer range transmission.

The WiFi 11ac supports AP/Bridge/AP Client modes can be diverse for most of wireless application. Client mode supports PMK\*\* Caching and pre-authentication. Working with load-Balancing "Priority" mode, the AP client can enable router to transmit on WiFi with first priority.

#### **Optional EMMC Flash storage\*\***

The optional EMMC flash storage on router can offer 8G/16G/32G capacity.

**MIMO technology with 3T3R and SMA/QMA\*\* type connectors**

Lantech TWMR-5002 series adapts MIMO technology with Smart antenna transmission and reception for 3T3R. With six external detachable antenna connectors (SMA/QMA\*\*) and optional antennas, TWMR-5002 can have better Wi-Fi & LTE/GPS coverage.

**Support AP/Bridge/Client mode, Mesh w/802.11k, v roaming**

TWMR-5002 supports AP/Bridge/Client mode for different applications. Client mode supports PMK\*\* Caching and pre-authentication.

It also supports 802.11k, v roaming to allow encryption keys to be stored on all of the APs in a network.

**Built-in Wireless Mesh network (WMN)**

TWMR-5002 supports Mesh network composed of different nodes. The set of SSIDs allow the wireless client to roam freely without the need for complicated account management. With Mesh protocol, it can provide a reliable, scalable, stable and seamless network topology.

**Wireless WMM QoS**

TWMR-5002 supports 802.11e standard which defines a set of Quality of Service for wireless LAN applications as well as WMM (WiFi multimedia)

**Advanced security & 16 SSIDs**

The security support standards including 64/128bits WEP, WPA/WPA2 PSK (TKIP, AES), 802.1x ensures the best security and active defense against security threats. Lantech TWMR-5002 support up to 16 SSIDs, each SSID has its independent security and encryption.

**Load Balancing with 8 mechanism for multi-WANs (premium license)**

TWMR-5002 supports Load Balancing for LTE / WAN connections. There are eight schemes for Load Balancing function:

Pack	Algorithm	Description
Basic Package	Fixed	Manually route by traffic type through fixed WAN link.
	Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activate another link if preferred link fail occurs. Once failover will not failback until link loss.
	Priority	Routes connections through preferred WAN link as primary while others follow by. Ex. Wi-Fi client>LTE>others
	Weighted Round-	Evenly distribute the traffic over all working WAN links in circular

	Robin	order according to the specified weights.
	Custom Route	Routing through the selected WAN for each specific traffic, ex: TCP/UDP port number and IP address.
Full Package** (incl. basic package)	Sticky Session*	Binding all connections in an application session to particular WAN link to ensure all connections in the session are routed to the same WAN link, that is suitable for security services like online payment etc.
	Smallest Load*	Routes connections through the WAN link with highest free bandwidth ratio. The ratio = 1 - (traffic load / the capability of a WAN link). The traffic load could be defined by downstream, upstream or total traffic
	Fastest*	Routes connections through the WAN link with lowest latency time.

**2 port serial connection, Modbus gateway**

It builds in 2 port serial connection for RS232 or RS422, RS485 in which RS422/RS485 has 2.5KV isolation protection.

The built-in Modbus gateway can convert Modbus RTU/ASCII to Modbus TCP for device control.

**VPN and firewall**

Besides traditional VPN peer to peer tunneling, TWMR-5002 support latest Multi-Site VPN function that is an efficient way for Mesh tunneling. The registration is under cloud service and encrypted by SSH makes the connection easy and safe.

It supports Multi-Site VPN, OpenVPN, L2TP over IPsec, IPsec, PPTP\*\*, L2 over GRE, IPGRE, and NAT for various VPN applications.

The built-in Layer-4 firewall includes DDoS, IP address filter / Mac address filter / TCP / UDP port number.

**DIDO for alarm & email notice; Event log; Remote Web control**

2 sets of DIDO function can support additional high/low physical contact for designate applications besides Port / Power events, for example, DIDO function can trigger alarm if the router was moved or stolen. In case of events, the TWMR-5002 will immediately send email and trap.

When the router is at remote area with limited access, Web control can help to get router status or remotely reboot by Web

**Wide range dual input voltage from 16.8-137.5V (WV model)**

The TWMR-5002 is able to work from dual 16.8V ~137.5V DC input (WV model) that is particular good for vehicle, rail train, depot etc applications.

**Environmental monitoring for inside router info& alerting; LTE/WIFI signal strength**

The built-in environmental monitoring can detect router overall temperature, voltage, current where can send the syslog and email when abnormal.

The graphic LTE/WIFI signal strength shows connection status at a glance.

**USB port for back up, restore configuration and upgrade firmware; Dual image firmware\***

The built-in USB port can upload/download the configuration through USB dongle for router replacement

**Dual image firmware\***

It supports dual-image firmware to choose which one to start.

**Editable login page of captive portal**

The TWMR-5002 supports editable captive portal function that allows administrator to force end-users redirect to authentication page.

**Ruggedized EN50155 design and FCC/CE, E-marking\*\* certificate**

The TWMR-5002 series is verified with EN50155, IEC61373, EN45545 standard with IP65/54 housing. It passed tests under extensive Industrial EMI and environmental vibration and shocks standards. With CE & FCC radio certification for WiFi and LTE and E-marking\*\* certificate, the TWMR-5002 is best for outdoor community, vehicle, power substation, process control automation etc. For more usage flexibilities, TWMR-5002 supports operating temperature from -40°C to 65°C.

**FEATURES & BENEFITS**

- High Speed Air Connectivity: WLAN interface support up to 1.3GMbps link speed(1AC)
- Built-in two Gigabit ports X-coded ; 1LAN+1WAN or 2LAN
- EMMC-FLASH storage\*\*8/16/32G
- Dual band 2.4G and 5GHz with 802.11ac/a/b/g/n
- Support AP/Bridge/Client/MESH mode
- Support roaming with 802.11k & v
- Support 802.11s Wireless Mesh Network
- Support 2.4Ghz operating within the following frequency bands:
  - 2.412~2.472 GHz
- Support 5Ghz operating within the following frequency bands:
  - 5.180GHz~5.825GHz
- MIMO Smart antenna technology with 3T3R with 6 SMA/QMA\*\* type connectors for WiFi & LTE, GPS
- Output power < 24dBm
- Transmit power adjustment
- VAP (virtual access point) support up to 16 SSIDs
- Operation modes : AP/ Bridge/ AP Client
- Traffic control for each SSID\*\*
- Band preference for same SSID services on dual band\*\*
- Rate selection to disable low data rate access\*\*
- Highly Security Capability: WEP64/128bits/ WPA/ WPA-PSK (TKIP,AES)/ WPA2/ WPA2-PSK (TKIP,AES)
- HTTP/HTTPS/Telnet/SSH & Administration access
- Support IPv6 & IPv4 protocol
- Radius Authentication, EAP-TLS, EAP-TTLS, PEAP; SSID broadcast disable supported
- Multiple channel bandwidths of 20MHz and 40MHz for 2.4G.
- Multiple channel bandwidths of 20MHz, 40MHz and 80MHz for 5G only.
- Wi-Fi Multimedia (WMM) and 802.11e traffic prioritization

- One LTE 4G/3G w/ 2 SIM slots design for mobile redundancy
- GPS/ GLONASS (built-in LTE module) connection
- Load Balancing supports 8 mechanism between multiple WANs


Pack	Algorithm	Description
Basic Package	Fixed	Manually route by traffic type through fixed WAN link.
	Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activate another link if preferred link fail occurs. Once failover will not fallback until link loss.
	Priority	Routes connections through preferred WAN link as primary while others follow by. Ex. Wi-Fi client>LTE>others
	Weighted Round-Robin	Evenly distribute the traffic over all working WAN links in circular order according to the specified weights.
	Custom Route	Routing through the selected WAN for each specific traffic, ex: TCP/UDP port number and IP address.
Full Package** (incl. basic package)	Sticky Session*	Binding all connections in an application session to particular WAN link to ensure all connections in the session are routed to the same WAN link , that is suitable for security services like online payment etc.
	Smallest Load*	Routes connections through the WAN link with highest free bandwidth ratio. The ratio = 1 - (traffic load / the capability of a WAN link). The traffic load could be defined by downstream, upstream or total traffic

	Fastest*	Routes connections through the WAN link with lowest latency time.
--	----------	---

- Built-in 2 x serial ports(RS232/RS422/RS485)
- Serial port with 2.5KV isolation on RS422/RS485
- Supports 2DI / 2DO(Digital Input / Output)
- Support Multi-Site VPN for Mesh tunneling as well as Open VPN, L2TP over IPsec, IPsec, PPTP\*\*, L2 over GRE , IPGRE and NAT for secured network connection
- The built-in Layer-4 firewall includes DDoS, IP address filter / Mac address filter / TCP/UDP port number
- NAT/DMZ/Port Forwarding
- Built-in Modbus gateway converting Modbus RTU/ASCII to Modbus/TCP
- Event alerting by Syslog, SNMP Trap, Email, Relay ; Permanent local log rotation / Maxi 1K records
- Remote Web control to get status or re-boot by Web
- Built-in RTC to keep track of time always
- Support SNTP to synchronize system clock

- Support LLDP discovery protocol
- Support DHCP Server and Client
- Built-in environmental monitoring for system input voltage, current and ambient temperature; Able to set alert when abnormal
- Graphic LTE & WiFi signal strength
- Firmware upgradeable through TFTP/ HTTP
- Configuration backup and restoration
  - Supports editable configuration file for system quick installation
  - USB port to upload/download configuration by USB dongle
- Dual image firmware\*
- Support editable captive portal login page
- IP 65/54 housing for water proof environment
- Wall-mount installation
- EN45545-2 Fire & Smoke, EN50155 and EN61373 shock/vibration verification
- Operation temperature -40~65C

**DIMENSIONS (unit=mm)**



**SPECIFICATION**

WLAN Interface		Modulation	802.11b: DSSS 802.11a/g: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) 802.11n: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) 802.11ac: OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM)
Radio Frequency Type	DSSS, OFDM	Operating	IEEE 802.11 a/b/g/n ISM Band,
Wireless Standard	IEEE 802.11ac/n/a 5GHz IEEE 802.11b/g/n 2.4GHz		
Wireless bandwidth	5GHz: Up to 1300Mbps 2.4GHz: Up to 450Mbps		

Frequency	2.412GHz~2.472GHz, 5150MHz~5850MHz		
Transmission Rate	IEEE802.11ac: up to 1300Mbps IEEE802.11b: 1 / 2 / 5.5 / 11 Mbps IEEE802.11a/g: 6 / 9 / 12 / 18 / 24 / 36 / 48 / 54 Mbps IEEE802.11n: up to 450Mbps		
IEEE 802.11b/g/n(2.4Gbps)	<b>Output Power Tx +/- 2dB(per chain)</b> 18dBm @ 1~11Mbps 18dBm @ 6~54Mbps 20/20dBm @ MCS0~MCS7 (HT20/40) <b>Receiver Sensitivity Rx +/- 2dB</b> ≤ -95dBm @ 1~11Mbps ≤ -92dBm @ 6~18Mbps ≤ -88dBm @ 24Mbps ≤ -85dBm @ 36Mbps ≤ -81dBm @ 48Mbps ≤ -80dBm @ 54Mbps ≤ -94dBm @ MCS0 (HT20/40) ≤ -76dBm @ MCS7 (HT20/40)		
IEEE 802.11a/n/g/n(2.4Gbps)	<b>Output Power Tx +/- 2dB(per chain)</b> 18dBm @ 1~11Mbps 18dBm @ 6~54Mbps 20/20dBm @ MCS0~MCS7 (HT20/40) <b>Receiver Sensitivity Rx +/- 2dB</b> ≤ -95dBm @ 1~11Mbps ≤ -92dBm @ 6~18Mbps ≤ -88dBm @ 24Mbps ≤ -85dBm @ 36Mbps ≤ -81dBm @ 48Mbps ≤ -80dBm @ 54Mbps ≤ -94dBm @ MCS0 (HT20/40) ≤ -76dBm @ MCS7 (HT20/40)		
IEEE 802.11a/n/ac(5Gbps)	<b>Output Power Tx +/- 2dB(per chain)</b> 20dBm @ 6~24Mbps 16dBm @ 36~54Mbps 19/18dBm @ MCS0 (HT20/40) 16/16dBm @ MCS7 (HT20/40) 19/18/18dBm @ MCS0 (VHT20/40/80) 13/13/13dBm @ MCS8 (VHT20/40/80) 13/13dBm @ MCS9 (VHT40/80) <b>Receiver Sensitivity Rx +/- 2dB</b> ≤ -92dBm @ 6~18Mbps ≤ -86dBm @ 24Mbps ≤ -84dBm @ 36Mbps ≤ -81dBm @ 48Mbps ≤ -80dBm @ 54Mbps ≤ -93dBm @ MCS0 (HT20/40) ≤ -71dBm/≤ -80dBm @ MCS7 (HT20/40) ≤ -90dBm @ MCS0 (VHT20/40/80) ≤ -69dBm @ MCS8 (VHT20/40/80) ≤ -66dBm @ MCS9 (VHT40/80)		
Encryption Security	WEP : (64-bit ,128-bit key supported) WPA /WPA2 : IEEE802.11i(WEP and AES encryption) WPA-PSK (256-bit key pre-shared key supported) OKC** and 802.11** EAP-TLS,EAP-TTLS, and PEAP		
Wireless Security	SSID broadcast disable		
<b>Cellular Interface</b>			
Antenna Connector	Detachable antenna connectors x 3; SMA/QMA** type female connector (Main, Aux, GPS)		
Location Solutions	GPS, Glonass (EU/Americas) GPS, Glonass, Beidou, Galileo (APAC model only)		
Band Options	<b>Asia-Pacific (APAC model)</b> LTE = B1, B3, B5, B7, B8, B18, B19, B21, B28, B38 (TDD), B39 (TDD), B40 (TDD), B41 (TDD) DC-HSPA+/ HSPA+/ HSPA/ UMTS = B1, B5, B6, B8, B9, B19  <b>Europe &amp; North America (EUNA model)</b> LTE = B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41 (TDD) DC-HSPA+/ HSPA+/ HSPA/ UMTS = B1, B2, B3, B4, B5, B8  <b>World Wide (WW model)</b>		
		LTE = B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B18, B19, B20, B26, B28, B29, B30, B32, B41 (TDD), B42 (TDD), B43 (TDD), B46 (TDD), B48 (TDD), B66 WCDMA = B1, B2, B3, B4, B5, B6, B8, B9, B19	
		<b>Data Rates – LTE</b> <b>Asia-Pacific (APAC model)</b> Downlink (Cat 6): FDD: 300 Mbps TDD: 222 Mbps Uplink (Cat 6): FDD: 50 Mbps TDD: 26 Mbps  <b>Europe &amp; North America (EUNA model)</b> Downlink (Cat 6): FDD: 300 Mbps TDD: 222 Mbps Uplink (Cat 6): FDD: 50 Mbps TDD: 26 Mbps  <b>World Wide (WW model)</b> Downlink: Cat 12: 600 Mbps Cat 9: 450 Mbps Uplink: Cat 13: 150 Mbps	
<b>Software</b>			
IPv6/4	Present		
Operating Mode	AP/Bridge/Client/MESH modes		
Login Security	Supports IEEE802.1x Authentication/RADIUS		
Access Security	HTTP/HTTPS/Telnet/SSH & Administration; SNMP*v1/v2/v3 access for authentication via MD5/SHA(v3) and Encryption via DES/AES(v3)		
Protocol	PPPoE Client, DHCP server/client, Adjustable MTU, Port forwarding (NAPT), DMZ; NAT, SNTP, Firewall(Firewall(DDoS; IP address filter / Mac address filter / TCP/UDP port number), VRRP, DDNS		
Management	SNMP*v1, v2c, v3/ Web/Telnet/CLI		
Load Balancing	8 schemes for multiple WAN		
<b>Basic Package</b>			
Fixed	Manually route by traffic type through fixed WAN link.		
Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activate another link if preferred link failure occurs.		
Priority	Routes connections through preferred WAN link while others stand-by. Sequentially activate other links if overflow occurs.		
Weighted Round-Robin	Evenly distribute the traffic over all working WAN links in circular order according to the specified weights		
Custom Route	Routing through the selected WAN for each specific traffic ex: TCP/UDP port number and IP address.		
<b>Full Package** incl. basic package</b>			
Sticky Session*	Binding all connections in an application session to particular WAN link to ensure all connections in the session are routed to the same WAN link , that is suitable for security services like online payment etc.		
Smallest Load*	Routes connections through the WAN link with highest free bandwidth ratio. The ratio = 1 - (traffic load / the capability of a WAN link). The traffic load could be defined by downstream, upstream or total traffic		
Fastest*	Routes connections through the WAN link with lowest latency time.		
Roaming	802.11k & v		
MESH	Support 802.11s Wireless Mesh Network		
WMM	Wifi multimedia and 802.11e traffic prioritization		
Security	WEP64/128bits/ WPA/ WPA-PSK (TKIP,AES)/ WPA2/ WPA2-PSK (TKIP,AES)/SSH/SSL/HTTPS		
Authentication	Radius Authentication, EAP-TLS, EAP-TTLS, PEAP; SSID broadcast disable supported		
SSID	16 sets		
Client mode	PMK** Caching and pre-authentication.		
Timer	Built-in Real Time Clock to keep track of time always(RTC)		
Discovery	IEEE 802.1ab Link Layer Discovery Protocol (LLDP)		

SNMP trap	Device cold / warm start Port link up / link down DI / DO high / low	<b>LED Indicators</b>	
Environmental Monitoring	System status for input voltage, current , ambient temperature to be shown in GUI and sent alerting if any abnormal status	Power & system indicator	Per unit: Power 1 (Green), Power 2 (Green), P-Fail (Red) , System Ready(Green), Serial1/2(Green)
Graphic signal display	Graphic LTE & Wifi signal strength	10/100/1000Base-T(X) port indicator	Link/Activity (Green), Speed (Yellow)
Remote Web control	To reboot or get status of router by Web	SIM	Green for Link/Act
Captive portal	Editable captive portal login page	GPS	Green for Link/Act
Maintenance	Firmware upgradeable through TFTP/HTTP	WLAN LEDs	WLAN 1 ,Link /ACT : Green
Configuration backup & restore	Supports text configuration file for quick system installation USB port to upload/download configuration by USB dongle	Fault	Red: Ethernet link down or power down
<b>Physical Ports &amp; System</b>		<b>Fault contact</b>	
Connectors	10/100/1000T: 2x ports M12 8-pole X-coded with Auto MDI/MDI-X function (1LAN+1WAN or 2LAN) USB/Console connector: 1 x M12 8-pole A-coded DIDO : 1 x 5-pole terminal block Power Input connector : 1 x M12 4-pole A-coded Serial connector : 2 DB9 SIM card slots : 2 SMA/QMA** connector for LTE: 2 (female) SMA/QMA** connector for GPS: 1 (female) RP-SMA/QMA** connector for Wi-Fi: 3 (female)	Relay	Relay output to carry capacity of 1A at 24VDC
Serial Baud Rate	1000Kbps high data rate,250kbps normal for RS232 ; 20Mbps high data rate,250kbps normal for RS422/RS485	<b>Power</b>	
Serial Data Bits	5, 6, 7, 8	Input power	Dual DC input, 16.8VDC~137.5VDC for (WV model)
Serial Parity	odd, even, none, mark, space	Power consumption (Typ.)	18 Watts
Serial Stop Bits	1, 1.5, 2	<b>Physical Characteristic</b>	
RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND	Enclosure	IP 65/54 aluminum case
RS-422	Tx+, Tx-, Rx+, Rx-, GND	Dimension	178 (W) x 99 (D) x 103 (H) mm
RS-485 (2-wire)	Data+, Data-, GND	Weight	1000g
Isolation protection	RS422/RS485 2.5KV isolation; 8KV contact & 15KV air RS232 8KV contact and 15KV air ESD DIDO 3KV isolation Input power 1.5KVA isolation	<b>Environmental</b>	
DI/DO	2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 40 VDC, 200mA	Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
EMMC Storage**	8/16/32 GB	Operating Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
		Operating Humidity	5% to 95% Non-condensing
		<b>Regulatory approvals</b>	
		EMC	FCC Part 15 Class A, EN55032 , EN55024
		EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-6-2
		Radio Frequency	EN301 489-1, EN301 489-17, EN301 489-19, EN301 489-52, EN300 440, EN301 893, EN300 328, EN301 908-1, EN303 413, EN62311
		Safety	EN60950 (LVD), AS60950 (LVD)
		Stability Testing	EN61373 (Shock & Vibration)
		Verifications & report	EN50155, EN50121-3-2, EN50121-4 verification EN45545-2 R13/R22/R23/R24/R25 (EN ISO 4589-2, EN ISO 5659-2, NF X70-100-1 & 2) Fire & Smoke verification
		MTBF	565,049 Hrs (IEC62380 standards)
		Warranty	5 years

\*Future Release

\*\*Optional

**RF Performance Table**

	Data Rate	TX Power (per chain)	TX Power (3 chains)	Tolerance	RX Specifications Sensitivity	Tolerance
2.4GHz 802.11b	1Mbps	20dBm	25dBm	±2dB	-95dBm	±2dB
	2Mbps	20dBm	25dBm	±2dB	-94dBm	±2dB
	5.5Mbps	20dBm	25dBm	±2dB	-92dBm	±2dB
	11Mbps	20dBm	25dBm	±2dB	-90dBm	±2dB
2.4GHz 802.11g	6Mbps	21dBm	26dBm	±2dB	-94dBm	±2dB
	9Mbps	21dBm	26dBm	±2dB	-93dBm	±2dB
	12Mbps	21dBm	26dBm	±2dB	-92dBm	±2dB
	18Mbps	21dBm	26dBm	±2dB	-90dBm	±2dB
	24Mbps	21dBm	26dBm	±2dB	-88dBm	±2dB
	36Mbps	20dBm	25dBm	±2dB	-85dBm	±2dB
	48Mbps	19dBm	24dBm	±2dB	-81dBm	±2dB
	54Mbps	18dBm	23dBm	±2dB	-80dBm	±2dB
2.4GHz 802.11n HT20	MCS 0	21dBm	26dBm	±2dB	-94dBm	±2dB
	MCS 1	21dBm	26dBm	±2dB	-91dBm	±2dB
	MCS 2	21dBm	26dBm	±2dB	-89dBm	±2dB
	MCS 3	20dBm	25dBm	±2dB	-84dBm	±2dB
	MCS 4	20dBm	25dBm	±2dB	-83dBm	±2dB
	MCS 5	20dBm	25dBm	±2dB	-78dBm	±2dB
	MCS 6	18dBm	23dBm	±2dB	-78dBm	±2dB
	MCS 7	16dBm	21dBm	±2dB	-76dBm	±2dB
2.4GHz 802.11n HT40	MCS 0	20dBm	25dBm	±2dB	-92dBm	±2dB
	MCS 1	20dBm	25dBm	±2dB	-89dBm	±2dB
	MCS 2	20dBm	25dBm	±2dB	-87dBm	±2dB
	MCS 3	19dBm	24dBm	±2dB	-82dBm	±2dB
	MCS 4	19dBm	24dBm	±2dB	-80dBm	±2dB
	MCS 5	19dBm	24dBm	±2dB	-78dBm	±2dB
	MCS 6	18dBm	23dBm	±2dB	-77dBm	±2dB
	MCS 7	16dBm	21dBm	±2dB	-73dBm	±2dB

	Data Rate	TX Power (per chain)	TX Power (3 chains)	Tolerance	RX Specifications Sensitivity	Tolerance
5GHz 802.11a	6Mbps	20dBm	25dBm	±2dB	-94dBm	±2dB
	9Mbps	20dBm	25dBm	±2dB	-94dBm	±2dB
	12Mbps	20dBm	25dBm	±2dB	-92dBm	±2dB
	18Mbps	20dBm	25dBm	±2dB	-90dBm	±2dB
	24Mbps	20dBm	25dBm	±2dB	-86dBm	±2dB
	36Mbps	18dBm	23dBm	±2dB	-84dBm	±2dB
	48Mbps	16dBm	21dBm	±2dB	-81dBm	±2dB
	54Mbps	15dBm	20dBm	±2dB	-80dBm	±2dB
5GHz 802.11n/ac VHT20	MCS 0	19dBm	24dBm	±2dB	-93dBm	±2dB
	MCS 1	19dBm	24dBm	±2dB	-90dBm	±2dB
	MCS 2	19dBm	24dBm	±2dB	-87dBm	±2dB
	MCS 3	18dBm	23dBm	±2dB	-83dBm	±2dB
	MCS 4	18dBm	23dBm	±2dB	-80dBm	±2dB
	MCS 5	17dBm	22dBm	±2dB	-77dBm	±2dB
	MCS 6	16dBm	21dBm	±2dB	-74dBm	±2dB
	MCS 7	14dBm	19dBm	±2dB	-73dBm	±2dB
5GHz 802.11n/ac VHT40	MCS 0	18dBm	23dBm	±2dB	-90dBm	±2dB
	MCS 1	18dBm	23dBm	±2dB	-88dBm	±2dB
	MCS 2	18dBm	23dBm	±2dB	-85dBm	±2dB
	MCS 3	17dBm	22dBm	±2dB	-82dBm	±2dB
	MCS 4	17dBm	22dBm	±2dB	-80dBm	±2dB
	MCS 5	16dBm	21dBm	±2dB	-75dBm	±2dB
	MCS 6	15dBm	20dBm	±2dB	-73dBm	±2dB
	MCS 7	14dBm	19dBm	±2dB	-73dBm	±2dB
	MCS 8	13dBm	18dBm	±2dB	-70dBm	±2dB
	MCS 9	13dBm	18dBm	±2dB	-68dBm	±2dB
5GHz 802.11ac VHT80	MCS 0	18dBm	23dBm	±2dB	-89dBm	±2dB
	MCS 1	18dBm	23dBm	±2dB	-87dBm	±2dB
	MCS 2	18dBm	23dBm	±2dB	-85dBm	±2dB
	MCS 3	17dBm	22dBm	±2dB	-83dBm	±2dB
	MCS 4	17dBm	22dBm	±2dB	-80dBm	±2dB
	MCS 5	16dBm	21dBm	±2dB	-78dBm	±2dB
	MCS 6	15dBm	20dBm	±2dB	-75dBm	±2dB
	MCS 7	14dBm	19dBm	±2dB	-72dBm	±2dB
	MCS 8	13dBm	18dBm	±2dB	-70dBm	±2dB
MCS 9	13dBm	18dBm	±2dB	-68dBm	±2dB	

## ORDERING INFORMATION

All QMA connector models are with -Q model name.

- **TWMR-5002-1L-1AC-2S-WV-65-EUNA.....P/N: 8630-041**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS232 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; EU and US band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2S-WV-65-APAC.....P/N: 8630-042**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS232 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; APAC band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2S-WV-65-WW.....P/N: 8630-043**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS232 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; Worldwide band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2SA-WV-65-EUNA.....P/N: 8630-0411**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS422 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; EU and US band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2SB-WV-65-EUNA.....P/N: 8630-0412**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS485 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; EU and US band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2SA-WV-65-APAC.....P/N: 8630-0421**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS422 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; APAC band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing



- **TWMR-5002-1L-1AC-2SB-WV-65-APAC.....P/N: 8630-0422**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS485 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; APAC band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2SA-WV-65-WW.....P/N: 8630-0431**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS422 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; Worldwide band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2SB-WV-65-WW.....P/N: 8630-0432**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS485 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; Worldwide band; dual input 16.8V~137.5VDC; -40~65C; IP65 housing
- **TWMR-5002-1L-1AC-2S-WV-54-EUNA.....P/N: 8630-024**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS232 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; EU and US band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2S-WV-54-APAC.....P/N: 8630-023**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS232 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; APAC band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2S-WV-54-WW.....P/N: 8630-022**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS232 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; Worldwide band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2SA-WV-54-EUNA.....P/N: 8630-0211**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS422 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; EU and US band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2SB-WV-54-EUNA.....P/N: 8630-0241**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS485 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; EU and US band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2SA-WV-54-APAC.....P/N: 8630-0221**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS422 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; APAC band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2SB-WV-54-APAC.....P/N: 8630-0222**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS485 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; APAC band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2SA-WV-54-WW.....P/N: 8630-0231**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS422 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; Worldwide band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing
- **TWMR-5002-1L-1AC-2SB-WV-54-WW.....P/N: 8630-0232**  
EN50155 Multifunction VPN Router w/1 WIFI 11ac + 1 LTE 4G SMA connectors+ 2 serial RS485 ports + 2 Gigabit X-coded Ethernet for load-Balancing, VPN, Protocol Gateway; Worldwide band; dual input 16.8V~137.5VDC; -40~65C; IP54 housing

**EMMC Flash Storage**

- **8G.....P/N: 8850-113**
- **16G.....P/N: 8850-114**
- **32G.....P/N: 8850-115**

**Software License**

- **LOAD BALANCING Full Package.....P/N: 9000-102**

**OPTIONAL ACCESSORIES**

**Management System**

- **InstaAir.....P/N: 9000-121**  
Cloud Based Fleet Management System for Routers

**Multifunction Antenna**

- **ANT11000091** 5-in-1 omnidirectional antenna – 2G/3G/4G (698-960/1710~2170/2300~2700MHz) MIMO x2 + Wi-Fi 2.4/5GHz MIMO x2 + GPS/GLONASS/GALILEO (1575.42/1602MHz) x1, 3dBi, IP67, cable length: 3M



- **ANT11000092** 6-in-1 omnidirectional antenna – 2G/3G/4G (698-960/1710~2170/2300~2700MHz) MIMO x2 + Wi-Fi 2.4/5GHz MIMO x1 + GPS/GLONASS/GALILEO/BeiDou (1561/1575.42/1602MHz) x1 + AM/FM x1 + DSRC x1, 6dBi, IP67, cable length: 30cm



**GPS Antenna**

- **ANT12000001** SMA GPS antenna, 28dB, 300m



**Cellular Antenna**

- **ANT11000041** 2G/3G/4G dipole antenna, 791-960/1710~2170/2500~2700MHz, 3dBi, SMA plug, EU



- **ANT11000042** 2G/3G/4G dipole antenna, 704-960/1710~2170MHz, 3dBi, SMA plug, US



- **ANT11000044** 2G/3G/4G dipole antenna, 704-960/1710~2690MHz, 1.6dBi, SMA plug, EU



- **ANT11000045** 2G/3G/4G dipole antenna, 698-960/1710~2690MHz, 3dBi, SMA plug, US



**Wi-Fi Antenna**

- **ANT11000051** 2.4/5GHz SMA dipole Wi-Fi antenna, 3dBi (2.4GHz), 4dBi (5GHz)



- **ANT11000055** 2.4/5GHz SMA dipole Wi-Fi antenna, 6dBi (2.4GHz), 4dBi (5GHz)



- **ANT11000090** 2.4/5GHz omnidirectional Wi-Fi antenna, 802.11ac 3x3 MIMO, 5dBi, IP67, cable length: 3M



**Antenna Base**

- **ADA11000052** Magnetic antenna base for Wi-Fi, RP SMA Jack Base, Length : 1M



■ **ADA11000053** Magnetic antenna base for 3G/4G, RP SMA Jack Base, Length : 1M



**Lantech Communications Global Inc.**

[www.lantechcom.tw](http://www.lantechcom.tw)  
[info@lantechcom.tw](mailto:info@lantechcom.tw)

© 2020 Copyright Lantech Communications Global Inc. all rights reserved.  
The revise authority rights of product specifications belong to Lantech Communications Global Inc.  
Lantech may make changes to specification and product descriptions at anytime, without notice.